



4 CONDUCTOR - BLACK, WHITE, RED, GREEN -
 RUBBER INSULATION #4 AWG - STRANDED
 BARE COPPER CONDUCTORS BLACK, TYPE
 SO JACKET 90 DEG.C, 600V

DO NOT SCALE WORK TO DIMENSIONS SHOWN			
BEND RADIUS UNLESS OTHERWISE NOTED: **		TOLERANCE UNLESS OTHERWISE SPECIFIED 0.X = ± 0.1 BEND RAD = ± 0.020 0.XX = ± 0.02 ANGLE = ± 1° 0.XXX = ± 0.005	
REMOVE ALL BURRS AND BREAK SHARP EDGES 0.010 X 45°		COMMERCIAL TOLERANCES APPLY TO SHEET METAL GAUGES, TUBING, ROLLED, DRAWN OR EXTRUDED SECTIONS AND STANDARD PARTS.	
THIS DRAWING AND INFORMATION THEREON IS THE CONFIDENTIAL PROPERTY OF THE HENNY PENNY CORPORATION AND ALL UNAUTHORIZED USE AND REPRODUCTION IS PROHIBITED.			

C	DIM. 108.0 WAS 84.0 UPDATE TITLE PER NAMING CONVENTION ** ** ** ** **	8/4/03	SLW	11920
REV	REVISION RECORD	DATE	ENG	PCN NO
	DRAWN BY M. SHIELDS	DATE 9/12/00	NEXT ASSEMBLY **	ENGINEER B. CASEY
	SCALE 1/8	SUPERSEDES **	FIRST USED ON FRY/OE-100	
		1219 US ROUTE 35 WEST EATON, OHIO 45320		
TITLE CORD-ELECTRIC				SHEET 1 OF 1
MATERIAL NOTED **		SIZE C	DRAWING NUMBER 54775	