CABLE TECHNOLOGY, INC.

73 RIVER ROAD - WILLINGTON, CT 06279 - (860) 429 - 7889 FAX (860) 429 - 3615

ALPHA EQUAL 5332C
CT-E2470

CONDUCTOR:	#24 7/32 TINNED COPPER INSULATED WITH .010” PVC
PAIRS:	TWIST TWO (2) CONDUCTORS TOGETHER
CABLING:	CABLE TWELVE (12) PAIRS TOGETHER TO FORM THE CORE
TAPE SEPARATOR:	WRAP CORE WITH A CLEAR MYLAR TAPE SEPARATOR
DRAIN:	PULL IN A #24 7/32 TINNED COPPER DRAIN WIRE BETWEEN SEPARATOR AND TAPE SHIELD
TAPE SHIELD:	WRAP WITH AN ALUMINUM/MYLAR/ALUMINUM TAPE SHIELD
SHIELD:	36 AWG TINNED COPPER BRAID, 70% MINIMUM COVERAGE
JACKET:	.063” CHROME PVC, PULL IN A NYLON RIP CORD UNDER JACKET (FOR EASE IN STRIPPING)
NOM OD:	.460”
PRINT IN WHITE: (1329)	E151405 24 AWG TYPE CM 105°C (UL)...AWM 2343...C(UL) CMG FT-4...CE...ROHS

COLOR CODE PAIRS:

1) WHITE / BLACK
2) WHITE / BROWN
3) WHITE / RED
4) WHITE / ORANGE
5) WHITE / YELLOW
6) WHITE / GREEN
7) WHITE / BLUE
8) WHITE / VIOLET
9) WHITE / GRAY
10) BLACK / BROWN
11) BLACK / RED
12) BLACK / ORANGE