

3C12 & 2C22 SHIELDED COMPOSITE CABLE CT-E593B

CONDUCTORS:THREE (3) #12 65/30 TINNED COPPER INSULATED WITH .016" PVC
(PER UL1569/1007)
CC: BLACK, RED, WHITETWO (2) #22 7/30 TINNED COPPER INSULATED WITH .016" PVC

TWO (2) #22 7/30 TINNED COPPER INSULATED WITH .016" PVC (PER UL1569/1007) CC: ORANGE, BROWN

- <u>CABLING</u>: CABLE THE FIVE CONDUCTORS TOGETHER
- DRAIN: #16 26/30 TINNED COPPER DRAIN WIRE

TAPE SHIELD:WRAP WITH AN ALUMINUM/POLYESTER TAPE SHIELD, FOIL
FACING IN, IN CONTACT WITH DRAIN WIRE (100% COVERAGE, 25%
OVERLAP)


JACKET: .035" CHROME PVC

<u>NOM OD</u>: .350" -.020" / +.015"

PRINT IN WHITE: E83208 RU AWM STYLE 2661 105°C 300V VW-1...ROHS

(0457-NW)

RATINGS: MEETS OR EXCEEDS NFPA-79 and 60204 ROHS COMPLIANT UL AWM 2661 105C 300V VW-1



5/1/2015 REVISED OD & TOLERANCES