


## Specification Sheet

Part Number: CTM410C2



<b>Article Number</b>	151-30703
<b>Type</b>	CTM4
<b>Color</b>	White (WH)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Designed for use with 18 through 120 pound cable ties to provide stability when securing bundles.</li><li>• Secures with a single screw providing quick installation.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	HellermannTyton cable tie mounts are designed for use with 18 through 120 pound cable ties to provide stability when securing bundles. The mounts are installed quick and easy by securing a single screw.
<b>Short Description</b>	Cable Tie Anchor Mount, .86" x .62", .25" Hole Dia, .31" Max Tie Width, PA66, White, 100/pkg

**Global Part Name**

CTM4-PA66-WH

**Length L (Imperial)**

0.86

**Length L (Metric)**

21.8

**Fixation Method**

Screw Mounting and Rivet

**Width W (Imperial)**

0.62

**Width W (Metric)**

15.8

**Cable Ties**

T18 - T120

**Height H (Imperial)**

.37

**Height H (Metric)**

9.40

**Cable Tie Width Max (Imperial)**

0.31

**Cable Tie Width Max (Metric)**

7.9

**Mounting Hole Diameter D (Imperial)**

0.25

**Mounting Hole Diameter D (Metric)**

6.4 mm

**Mounting Hole Diameter D Max (Metric)**

6.4

**Material**

Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Flammability** UL 94 V2

**Operating Temperature (Metric)** -40°F to +185°F (-40°C to +85°C)

**Reach Complaint(Article 33)** Yes

**ROHS Complaint** Yes

**Certification/Specification WEB** UL | ANSI/UL 62275 UL | ANSI/UL 746B UL | ANSI/UL 1565

**UL Recognized (US)** Yes

**UL Recognized (US and Canada)** Yes

**Package Quantity(Imperial)** 100

**Package Quantity (Metric)** 100

**Customs Number** 3926909987

**Content Unit(BMEcat)** pcs.