## HellermannTyton

## CTN340STD

110540010	
Ar	ticle Number: 169-60013
10m	onvoluted Tubing, Slit, 3/4" Dia., PA6, Black w/Gray Stripe, 550ft/Carton
	RoHS
-	l spec sheet
se Data Local Order Number	CTN340STD
Туре	CTN340
Color	Black with Gray Stripe (BKSTGY)
Features and Benefits	<ul> <li>Durable tubing provides protection of wire harness from friction, vibration, fraying and puncture</li> <li>Tubing protects cables and wires against automotive fluids, vibration wear</li> <li>Weather resistant material provides protection against water, snow, ice, and the effects of heat, cold, and sunlighted against water.</li> </ul>
Product Description	HellermannTyton's Convoluted Tubing, also known at Split Loom Tubing, provides an efficient method of routing a protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entir assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offer's excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.
Short Description	Convoluted Tubing, Slit, 3/4" Dia., PA6, Black w/Gray Stripe, 550ft/Carton

## **Product Dimensions**

Length L (Imperial)	500.0 ft
Length L (Metric)	152.4 m
Inner Diameter D (Imperial)	0.759 "
Inner Diameter D (metric)	19.28 mm
Diameter D (imperial)	0.989 "
Diameter D (metric)	25.12 mm
Diameter D2 (imperial)	0.759 "
Diameter D2 (metric)	19.28 mm
Outside Diameter D (imperial)	0.989 "
Outside Diameter D (metric)	25.12 mm
Nominal Diameter (Imperial)	3/4 "
Nominal Diameter (Metric)	19.05 mm
Wall Thickness WT (Imperial)	0.005 "
Wall Thickness WT (Metric)	0.127 mm

## Logistics and Packaging

Quantity Per	carton
Package Quantity (Imperial)	550.0 ft
Package Quantity (Metric)	167.6 m
Carton Quantity	550

Material	Polyamide 6 (PA6)
Material Shortcut	PA6
Flammability	UL94 HB
Operating Temperature	-40°F to +300°F (-40°C to +149°C)
ROHS compliant (Article 4 - 1)	Yes

© HellermannTyton 2015