

Specification Sheet

Part Number: CTP1120STD



Article Number	169-60503
Туре	CTP1120
Color	Black (BK)
Features & Benefits	• Split side is ideal for applications where braided tubing or spiral wrap may be difficult to install. • Tubing provides full coverage where spiral wrap or other coverings may not be suitable. • In harsh applications the tubing provides resistance to crushing, impact, and abrasion. • Tubing offers excellent protection against automotive fluids, vibration wear, water, snow, ice, and the effects of heat, cold, and sunlight on cables and wires.
Quantity Per	carton

Troduct Sescription	provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offer's excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.			
Short Description	Convoluted Tubing, Slit, 1.5" Dia, PE, Black, 150ft/carton			
Global Part Name	CTP1120-PE-BK			
Technical Description	Convoluted Tubing, Slit, 1-1/2" Dia., PE, Black			
Length L (Imperial)	150.0			
Length L (Metric)	45.7			
Inner Diameter D (Imperial)	1.647			
Inner Diameter D (Metric)	41.83			
Diameter D (imperial)	1.947			
Diameter D (metric)	49.45			
Outside Diameter OD(Imperial)	1.947			

HellermannTyton's Convoluted Tubing, also known at Split Loom Tubing,

Nominal Diameter (Imperial)

Outside Diameter OD(metric)

Product Description

1.5

49.45

Wall Thickness WT (Imperial)	.006
Wall Thickness WT (Metric)	0.152
Material	Polyethylene (PE)
Material Shortcut	PE
Flammability	UL 94 V2
Halogen free	No
Operating Temperature (Metric)	-40°F to +199°F (-40°C to +93°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	150
Package Quantity (Metric)	45.72
Customs Number	3926909987