

Specification Sheet

Part Number: CTP120STD



Article Number	169-60507			
Туре	CTP120			
Color	Black (BK)			
Features & Benefits	• Split side is ideal for applications where braided tubing or spiral wrap may be difficult to install • Tubing provides full coverage where spiral wrap or other coverings may not be suitable • In harsh applications the tubing can provide resistance to crushing, impact, and abrasion • Tubing offers excellent protection against automotive fluids, vibration wear, water, snow, ice, and the effects of heat, cold, and sunlight on cables and wires			
Quantity Per	carton			

Product Description	HellermannTyton's Convoluted Tubing, also known at Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offer's excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.
Short Description	Convoluted Tubing, Slit, .5" Dia, PE, Black, 1100 ft/carton
Global Part Name	CTP120-PE-BK
Technical Description	Convoluted Tubing, Slit, 1/2" Dia., PE, Black

Length L (Imperial)	1100.0
Length L (Metric)	335.3
Inner Diameter D (Imperial)	0.516
Inner Diameter D (Metric)	13.11
Diameter D (imperial)	0.70
Diameter D (metric)	17.78
Outside Diameter OD(Imperial)	0.70
Outside Diameter OD(metric)	17.78
Nominal Diameter (Imperial)	0.5

12.70

Nominal Diameter (Metric)

Wall Thickness WT (Imperial)	.005
Wall Thickness WT (Metric)	0.127
Material	Polyethylene (PE)
Material Shortcut	PE
Flammability	UL 94 V2
Halogen free	No
Operating Temperature (Metric)	-40°F to +199°F (-40°C to +93°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	1100
Package Quantity (Metric)	335.30
Customs Number	3926909987