

CTT60R0HSM4



Article Number: 112-52114

Compression Tie, 8" Long, 60lb Tensile Strength, PA66HS, Black, 1000/pkg



[Download drawing](#)



[Download spec sheet](#)

Base Data

Local Order Number CTT60R0HSM4

Type CTT60R

Color Black (BK)

- Features and Benefits**
- Heat stabilized cable ties provide excellent resistance to high heat exposures.
 - Head design contains clamping rails to provide full circumferential compression around bundles.
 - Bent tail allows for quick insertion into head.

Product Description The 360 Degree compression ties were designed with underside clamping rails to allow for optimal surface contact and complete circumferential compression around the bundle. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Compression Tie, 8" Long, 60lb Tensile Strength, PA66HS, Black, 1000/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 60.0 lbs

Minimum Tensile Strength (Metric) 265.0 N

Length L (Imperial) 8.0 "

Length L (Metric) 205.0 mm

Width W (Imperial) 0.19 "

Width W (Metric) 4.7 mm

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.5 mm

Bundle Diameter Max. (Imperial) 1.8 "

Bundle Diameter Max. (Metric) 45.0 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 1000

Carton Quantity 5000

Material and Specifications

Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
CSA Certified	No
Flammability	UL94 V2
Operating Temperature	-40°F to +257°F (-40°C to +125°C)
ROHS compliant (Article 4 - 1)	Yes
Certification/Specification	UL
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	Yes