



ADVANCED CABLE TIES PART NUMBER	SCREW SIZE	A - WIDTH IN (mm)	B - CLOSED DIAMETER IN (mm)	C - CENTER TO CENTER IN (mm)	D - OVERALL LENGTH IN (mm)	E - THICKNESS IN (mm)	ANSI/UL 94 MH FLAMABILITY RATING
AP(R, L)-CCL-125	#8	.377 (9.600mm) +/- .014 (.36mm)	.129 (3.300mm) +/- .011 (.300mm)	.314 (8.0mm) +/- .014 (.360mm)	.665 (16.900mm) +/- .005 (.130mm)	.047 (1.200mm) +/- .009 (.250mm)	UL 94-V2
AP(R, L)-CCL-187	#8	.377 (9.600mm) +/- .014 (.36mm)	.208 (5.300mm) +/- .011 (.300mm)	.362 (9.200mm) +/- .014 (.360mm)	.728 (18.5mm) +/- .020 (.520mm)	.047 (1.200mm) +/- .009 (.250mm)	UL 94-V2
AP(R, L)-CCL-250	#8	.397 (10.100mm) +/- .013 (.350mm)	.267 (6.800mm) +/- .009 (.250mm)	.409 (10.4mm) +/- .013 (.350mm)	.787 (20.000mm) +/- .019 (.500mm)	.047 (1.200mm) +/- .009 (.250mm)	UL 94-V2
AP(R, L)-CCL-312	#8	.394 (10.00mm) +/- .017 (.430mm)	.330 (8.4mm) +/- .014 (.360mm)	.441 (11.200mm) +/- .017 (.430mm)	.889 (22.600mm) +/- .020 (.520mm)	.047 (1.200mm) +/- .004 (.100mm)	UL 94-V2
AP(R, L)-CCL2-375	#8	.472 (12.300mm) +/- .017 (.430mm)	.425 (10.800mm) +/- .017 (.430mm)	.492 (12.500mm) +/- .017 (.430mm)	1.047 (26.600mm) +/- .020 (.520mm)	.055 (1.400mm) +/- .004 (.100mm)	UL 94-V2
AP(R, L)-CCL2-500	#8	.480 (12.200mm) +/- .017 (.430mm)	.543 (13.800mm) +/- .017 (.430mm)	.582 (14.800mm) +/- .017 (.430mm)	1.193mm (30.300mm) +/- .020 (.520mm)	.055 (1.400mm) +/- .004 (.100mm)	UL 94-V2
AP(R, L)-CCL2-625	#8	.488 (12.400mm) +/- .017 (.430mm)	.685 (17.400mm) +/- .017 (.430mm)	.622 (15.800mm) +/- .017 (.430mm)	1.283 (32.600mm) +/- .024 (.620mm)	.055 (1.400mm) +/- .004 (.100mm)	UL 94-V2
AP(R, L)-CCL2-750	#8	.464 (11.800mm) +/- .017 (.430mm)	.783 (19.900mm) +/- .017 (.430mm)	.708 (18.000mm) +/- .017 (.430mm)	1.468 (37.300mm) +/- .024 (.620mm)	.055 (1.400mm) +/- .006 (.150mm)	UL 94-V2
AP(R, L)-CCL2-1000	#8	.472 (12.000mm) +/- .017 (.430mm)	1.070 (27.200mm) +/- .020 (.520mm)	.827 (21.000mm) +/- .020 (.520mm)	1.708 (43.400mm) +/- .024 (.620mm)	.055 (1.400mm) +/- .006 (.150mm)	UL 94-V2
AP(R, L)-CCL2-1250	#8	.472 (12.000mm) +/- .013 (.350mm)	1.331 (33.800mm) +/- .024 (.620mm)	1.023 (26.000mm) +/- .020 (.520mm)	2.059 (52.300mm) +/- .029 (.740mm)	.063 (1.600mm) +/- .004 (.100mm)	UL 94-V2
AP(R, L)-CCL2-1500	#8	.492 (12.500mm) +/- .017 (.430mm)	1.649 (41.900mm) +/- .024 (.620mm)	1.094 (27.800mm) +/- .020 (.520mm)	2.295 (58.3mm) +/- .029 (.740mm)	.059 (1.500mm) +/- .006 (.150mm)	UL 94-V2



ADVANCED CABLE TIES – CABLE CLAMPS

COLOR DESIGNATIONS:

0 = BLACK 9 = NATURAL

MATERIAL:

NYLON 6/6 POLYAMIDE

B	4/27/17	JA	JA	KT	NEW LOGO ADDED.	SHEET 1 OF 1	REV.: B	DRAWING NO.: CLAMPS-B	
A	4/22/14	JA	KT	KT	INITIAL RELEASE	DRAWN BY	DATE	CHECK	SCALE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION	JA	4/27/17	KT	NONE

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.

SPC-4.10.79.1