

EPDM - Welding Cable Class M

Flexible Welding Cable

UL: -50°C to 90°C, 600V, RHH/RHW

CSA: -50°C to 90°C, 600V, FT1



IEWC Part Number	AWG	Stranding	Nominal Insulation Thickness		Nominal O.D.		Approx. Weight	
			in	mm	in	mm	lbs/1k ft	kg/km
WC06	6	660/34	0.060	1.5	0.370	9.4	125	186
WC04	4	1045/34	0.060	1.5	0.415	10.5	191	284
WC02	2	1666/34	0.060	1.5	0.475	12.1	259	385
WC01	1	2090/34	0.080	2.0	0.530	13.5	331	493
WC1/0	1/0	2640/34	0.080	2.0	0.575	14.6	401	597
WC2/0	2/0	3300/34	0.080	2.0	0.630	16.0	511	760
WC3/0	3/0	4180/34	0.080	2.0	0.700	17.8	615	915
WC4/0	4/0	5225/34	0.080	2.0	0.800	20.3	844	1,256

Notes

- Soft-annealed, bare copper conductor
- Ethylene propylene diene monomer (EPDM) insulation
- RoHS Compliant
- MSHA Approved
- Standard insulation colors: orange and black

Alternative Constructions

- Additional strand counts available
- Temperature range down to -55°C and up to 105°C

Applications

For use in welding applications. Rated for continuous use from -50°C up to 90°C.