

Sound and Security Cables

RISER FR PVC JACKET
 UL TYPE CL3R/FPLR/CMR
 C(UL) CMG 300 VOLT



Applications

- Intercom/PA Systems
- Sound/Audio Systems

Characteristics

Operating Temperature:

- -10°C to +75°C

Voltage Rating:

- 300 Volts

Color Description:

- Chart A, Page 41

Product Description:

- Stranded Bare Copper
- Insulation: Semi-Rigid PVC
- Nylon Ripcord for Ease of Jacket Stripping
- Jacket: Flame-Retardant PVC

Specifications:

- UL Type CL3R /FPLR /CMR
- C(UL) CMG
(14 AWG CL3R/FPLR only)
- Passes UL 1666 Flame Test
- RoHS Compliant

Riser Sound and Security Cable

Part No.	No. of Cond.	Jacket Thickness (inches)	Jacket Color	Nominal Diameter (inches)
22 AWG 7-Strand Bare Copper				
32772	2	.014	Chrome Gray	.111
32774	4	.014	Chrome Gray	.128
32776	6	.014	Chrome Gray	.153
32778	8	.014	Chrome Gray	.165
18 AWG 7-Strand Bare Copper				
32794	2	.014	Chrome Gray	.148
32795	3	.014	Chrome Gray	.158
32796	4	.014	Chrome Gray	.172
32798	6	.014	Chrome Gray	.208
32800	8	.014	Chrome Gray	.227
16 AWG 19-Strand Bare Copper				
32836	2	.014	Chrome Gray	.182
32837	4	.014	Chrome Gray	.214
14 AWG 19-Strand Bare Copper				
32840	2	.014	Chrome Gray	.212