





Aerospace Part#: 8222 HOOK UP WIRE

DESCRIPTION

1 Conductor AWG 22/7x30 TC UL 1333 Application Hook Up Wire FEP

PHYSICAL PROPERTIES

Conductors	Insulation					
# Conductors	AWG	Material	Material	Wall	Finished OD	
1	22/7x30	Tinned Copper	FEP	.013"	.056"	

MECHANICAL PROPERTIES

Operating Temp	Total Weight	Bend Radius
UL Rated -80C to 150C	3.9 lbs/m	10 X OD

ELECTRICAL PROPERTIES

Max. Operating Voltage				
UL Rated 300 Volts				

INDUSTRY APPROVALS AND COMPLIANCE

Standards & Environmental Programs

Otanida de Environmenta i rogianis				
(UL) AWM STYLE	1333			
Reach / RoHS Compliant	YES			
Suitability	Direct Burial, Wet Location			
Resistance	Oil, Gas, Sunlight, Abrasian, Acid			
Flame Test	VW-1 / UL 1581			

MISCELLANEOUS

Markings: (UL) TAGS ON REEL

Color: TBD

Contact Us For More Information

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA

^{*} Specification subject to error and may change without notice