

# Sound and Security Cables

**PLENUM LOW-SMOKE  
PVC JACKET**  
UL TYPE CL3P/FPLP/CMP  
C(UL) CMP 300 VOLT



## Applications

- Intercom/PA Systems
- Sound/Audio Systems

## Characteristics

### Operating Temperature:

- -10°C to +75°C

### Voltage Rating:

- 300 Volts

### Color Description:

- Chart A, Page 41

### Product Description:

- Solid, Stranded Bare Copper
- Insulation: Plenum Low-Smoke PVC
- Nylon Ripcord for Ease of Jacket Stripping
- Jacket: Plenum Low-Smoke PVC

### Specifications:

- UL Type CL3P/FPLP
- C(UL)US CMP (14 and 12 AWG UL only)
- Passes NFPA 262 (UL 910) Flame Test
- RoHS Compliant

\* Color Code: Black, Red

## Plenum Sound and Security Cable

Part No.	No. of Cond.	Jacket Thickness (inches)	Jacket Color	Nominal Diameter (inches)
<b>22 AWG 7-Strand Bare Copper</b>				
34950	2	.014	White	.111
34952	4	.014	White	.128
34954	6	.014	White	.153
34956	8	.014	White	.165
<b>18 AWG 7-Strand Bare Copper</b>				
*34842	2	.014	White	.148
38748	2	.014	White	.148
34843	3	.014	White	.158
34844	4	.014	White	.172
34846	6	.014	White	.208
34848	8	.014	White	.227
34850	10	.014	White	.268
<b>18 AWG Solid Bare Copper</b>				
34829	2	.014	White	.136
34830	3	.014	White	.145
34833	6	.014	White	.190
32178	8	.014	White	.207
32180	10	.014	White	.244
<b>16 AWG 19-Strand Bare Copper</b>				
*32282	2	.014	White	.182
32284	4	.014	White	.214
<b>14 AWG 19-Strand Bare Copper</b>				
*32208	2	.014	White	.212
38752	2	.014	White	.212
32209	3	.014	White	.227
32210	4	.014	White	.250
<b>12 AWG 19-Strand Bare Copper</b>				
32729	2	.014	White	.248