


# Polyrad® XT Flexible Wire and Cable

2000V, Single Conductor, Dual Rated – 125°C/110°C



2000 VOLT CHART – STANDARD INSULATION THICKNESS

CATALOG NUMBER STOCK*	CONDUCTOR (AWG/kcmil) SIZE AND STRANDING		NOMINAL CONDUCTOR DIAMETER		NOMINAL INSULATION THICKNESS		NOMINAL CABLE DIAMETER		COPPER WEIGHT		NET CABLE WEIGHT		AMPACITY (Free Air 40°C Ambient)	
	INCHES	MM	MILS	MM	INCHES	MM	lbs./1000'	kg/km	lbs./1000'	kg/km	110°C	125°C		
364980	20	19/32	0.038	0.95	45	1.14	0.128	3.25	4	6	10	15	24	26
300620*	18	19/30	0.048	1.21	45	1.14	0.138	3.51	6	9	14	21	30	32
300890*	16	19/29	0.054	1.37	45	1.14	0.144	3.66	8	12	16	24	35	38
280740*	14	19/27	0.067	1.70	45	1.14	0.157	3.99	12	18	22	33	41	44
303480*	12	19/25	0.086	2.18	45	1.14	0.176	4.47	19	28	31	46	52	56
301260*	10	27/24	0.117	2.97	45	1.14	0.207	5.26	34	50	47	70	73	79
269970*	8	37/24	0.135	3.43	55	1.40	0.245	6.22	47	70	66	98	85	92
297970*	6	61/24	0.174	4.42	55	1.40	0.284	6.96	76	114	100	149	120	130
355490	5	91/24	0.219	5.56	55	1.40	0.329	8.36	116	173	144	214	160	173
301270*	4	105/24	0.262	6.65	55	1.40	0.372	9.45	137	204	169	252	168	181
325290	3	125/24	0.285	7.24	55	1.40	0.395	10.03	167	249	197	293	199	215
302440*	2	150/24	0.307	7.80	55	1.40	0.417	10.59	190	283	226	336	214	231
355500*	1	225/24	0.380	9.65	65	1.65	0.510	12.95	287	427	353	525	268	289
296500*	1/0	275/24	0.410	10.41	65	1.65	0.540	13.72	351	522	420	625	304	328
301280*	2/0	325/24	0.470	11.94	65	1.65	0.600	15.24	407	606	481	716	338	364
300900*	3/0	450/24	0.549	13.94	65	1.65	0.679	17.25	594	884	663	987	414	446
296510*	4/0	550/24	0.593	15.06	65	1.65	0.723	18.36	696	1036	792	1179	472	509
267040	262	650/24	0.630	16.00	75	1.91	0.780	19.81	820	1220	931	1386	524	565
296520*	313	775/24	0.685	17.40	75	1.91	0.835	21.21	987	1469	1108	1649	590	636
304020	373	925/24	0.750	19.05	75	1.91	0.900	22.86	1176	1750	1310	1950	657	708
300180	444	1100/24	0.820	20.83	75	1.91	0.970	24.64	1413	2207	1561	2323	734	791
263400	535	1325/24	0.895	22.73	90	2.29	1.075	27.31	1697	2525	1898	2810	828	893
355570	646	1600/24	0.980	24.89	90	2.29	1.160	29.46	2020	3006	2231	3320	931	1004
260080	777	1925/24	1.075	27.31	90	2.29	1.255	31.88	2435	3624	2681	3990	1047	1129
355600	929	2300/24	1.230	31.24	90	2.29	1.410	35.81	3117	4638	3431	5106	1168	1259
355620	1111	2750/24	1.328	33.73	110	2.79	1.548	39.32	3400	5060	3972	5911	1254	1352

2000 VOLT CHART – HEAVY WALL INSULATION THICKNESS

355510	4/0	550/24	0.593	15.06	105	2.67	0.803	20.40	696	1036	837	1246	472	509
355520	262	650/24	0.630	16.00	105	2.67	0.840	21.34	820	1220	969	1442	524	565
355530	313	775/24	0.685	17.40	105	2.67	0.895	22.73	987	1469	1149	1710	590	636
355540	373	925/24	0.750	19.05	105	2.67	0.960	24.38	1176	1750	1353	2013	657	708
355550	444	1100/24	0.820	20.83	105	2.67	1.030	26.16	1413	2207	1607	2392	734	791
355560	535	1325/24	0.895	22.73	120	3.05	1.135	28.83	1697	2525	1946	2896	828	893
355580	646	1600/24	0.980	24.89	120	3.05	1.220	30.99	2020	3006	2285	3400	931	1004
355590	777	1925/24	1.075	27.31	120	3.05	1.315	33.40	2435	3624	2727	4058	1047	1129
355610	929	2300/24	1.230	31.24	120	3.05	1.470	37.34	3117	4638	3539	5267	1168	1259
355630	1111	2750/24	1.328	33.73	120	3.05	1.568	39.83	3400	5060	4011	5969	1254	1352

Dimensions and weights are nominal; subject to industry tolerances.

Note #1: Where additional insulation thickness is desired for added mechanical protection, these values are noted in the second chart.

Note #2: At the option of the purchaser, the manufacturer's standard type of stranding will be acceptable providing that the conductor diameter does not exceed the values shown. The total number of wires shall be as specified, plus or minus one percent, except 150/24 which may vary by minus two percent, providing that the conductor diameter does not exceed the values shown.

\*Standard Stock Items

## Product Construction

### Conductor:

- 20 AWG thru 1111 kcmil soft annealed tinned copper per ASTM B33, B8 and B172

### Insulation:

- Polyrad XT flame-retardant, low-smoke irradiated Cross-Linked Polyolefin (XLPO)

### Print:

- GENERAL CABLE BRAND REX BRAND (WC) POLYRAD XT 125C/110C XXAWG 2000V YEAR/MONTH

### Options:

- Class K stranding
- Available in colors other than dark gray
- Cable meeting NYCTA TX specification available upon request

## Applications

- Ideally suited for use where environmental factors require cable characteristics to perform with a high degree of flame-retardancy and excellent moisture-stable electrical values. Where reliability is the major concern and where maximum performance will be demanded
- Engineered and manufactured for both original equipment and retrofit use in power and control circuits, and in motor leads
- Extensively found on all types of heavy- and light- rail cars, rapid transit cars, diesel-electric locomotives, freight cars, wayside equipment and off-road vehicles

## Features

- Dual temperature rating at 125°C/110°C for long life, higher ampacities and protection from thermal overloads
- Excellent flexibility and free stripping
- Higher ampacities and simplified installations possible due to small outside diameters, flexible stranding and insulation
- Outstanding thermal stability at elevated temperatures
- Maximum flame-retardance and low toxicity
- Excellent low-temperature performance; suitable for installation in sub zero conditions
- Extra tough, mechanically rugged irradiated thermoset insulation
- Resistant to most oils and chemicals
- Meets cold bend test at -55°C
- Meets cold impact test at -40°C

## Compliances

### Industry:

- AAR S-501/AAR RP-585
- ICEA S-95-658

### Flame Test:

- IEEE 1202 (70,000 BTU/hr)
- IEEE 383 (70,000 BTU/hr)
- VW-1

### Other:

- BSS 7239
- SMP 800-C
- ASTM E662
- Meets requirements of 49 CFR Part 238 for flame and smoke requirements

## Packaging

- Standard reel put-up