

METRIC MEASUREMENT VERSION

E508001 Cord Sets - DataTuff® Cat 5e 600V AWM IP67 RJ45 Cord Set



For more Information please call

1-800-Belden1



General Description:

1 meter (3.3 ft.), Shielded with solid conductors (ref: Belden Bonded-Pair Cable 7957A). Cable Rating NEC: CMR, CMX-Outdoor. CEC: CMR FT4. MSHA. Beldfoil® (100% coverage) and TC Braid (70% coverage) Shield. 600V AWM Rated.

EU Directive 2002/95/EC (RoHS):	Yes		
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2006		
MII Order #39 (China RoHS):	EUP 50		
es (Overall)			
Notes: For additional information about this product, visit ou	ir web site at http://www.beiden.com		
ble			
Description:	4 pair, 24 AWG Bare Copper, Polyolefin Insulation, Bonded pairs, Overall Beldfoil® and TC Braid Shield, Industrial Grade PVC, Oil Res, Sun Res, P-MSHA, CMR, CMXOutdoor, FT4, 600V AWM Rated.		
Part Number:	7957A		
Shielding:	Aluminum Foil-Polyester Tape/TC - Tinned Copper		
Electrical Performance:	Category 5e		
Maximum Operating Voltage:	300 V RMS (600 V AWM Rated)		
Applicable Standards:	ANSI/TIA/EIA-568-C.2, ISO/IEC 11801, EtherNet/IP(tm) Specification, UL 1666 Riser		
nnectors			
Description:	RJ45 plugs. Suitable for use in IP67 applications		
Connector Type:	Cat 5e		
Sealing:	Suitable for IP67		
Connector Interface:	IEC 60603-7		
Shielding:	Smooth Coated Aluminum		
Electrical Performance:	Cat 5e		
Maximum Operating Voltage:	300 V RMS		
Applicable Standards:	ANSI/TIA/EIA-568-C.2, ISO/IEC 11801, EtherNet/IP Specification		
sembly			
Part Number:	E508001		
Electrical Performance:	Category 5e		
Maximum Operating Voltage:	300 V RMS (600 V AWM Rated)		
Storage Temperature Range:	-40°C To +70°C		
Installation Temperature Range:	-10°C To +60°C		
Operating Temperature Range:	-10°C To +60°C		
Applicable Standards:	ANSI/TIA/EIA-568-C.2, ISO/IEC 11801, UL 1863 and CSA-22.2 No. 233		
Shielding:	Aluminum Foil-Polyester Tape/TC - Tinned Copper		
Length:	1 meter (3.3 ft.)		

Put Ups and Colors:

Detailed Specifications & Technical Data



METRIC MEASUREMENT VERSION

E508001 Cord Sets - DataTuff® Cat 5e 600V AWM IP67 RJ45 Cord Set

	Item #	Putup	Ship Weight	Color	Notes	Item Desc
--	--------	-------	-------------	-------	-------	-----------

Revision Number: 0 Revision Date: 08-20-2015

© 2015 Belden, Inc All Rights Reserved

All hough Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information and belief at the date of its publication. The information provided in this Product Disclosure, is denied on the product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product tiself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. product.