

Shielded Multi-Conductor FT-4



1-888-Electro
Fax 613-394-4101
 SALES@ELECTROCABLES.COM

Stranded Tinned Copper Conductors*
 SR-PVC Insulation, 100% Aluminum Foil Shield
 Stranded Tinned Copper Drain, Grey PVC Jacket FT-4
 -20° C to 105° C, Contact sales@electrocables.com for approval info

[Home](#)
[Electronic & Electrical Index](#)
[Search](#)
[Previous](#) [Next](#)
[Colour Code: ECI Chart 2](#)

ECI Catalogue Number	Conductor			Drain AWG Size	Wall Thickness		Nominal O.D. (inches)	Total Weight (lbs/km)	Colour Code
	No.	Size	Stranding		Insulation (inches)	Jacket (inches)			
5152019TFT4	19	20	7 x 28	22	.010	.030	.354	373	ECI Chart 2
5152020TFT4	20	20	7 x 28	22	.010	.030	.370	401	2
5152025TFT4	25	20	7 x 28	22	.010	.030	.396	467	2
5152030TFT4	30	20	7 x 28	22	.010	.030	.440	576	2
5151851TFT4	2	18	16 x 30	20	.012	.023	.197	107	Black/Red
5151803TFT4	3	18	16 x 30	20	.012	.023	.209	127	ECI Chart 1
5151804TFT4	4	18	16 x 30	20	.012	.023	.228	153	1
5151805TFT4	5	18	16 x 30	20	.012	.023	.233	166	ECI Chart 2
5151806TFT4	6	18	16 x 30	20	.012	.023	.251	192	2
5151807TFT4	7	18	16 x 30	20	.012	.023	.267	216	2
5151808TFT4	8	18	16 x 30	20	.012	.023	.282	238	2
5151809TFT4	9	18	16 x 30	20	.012	.023	.296	268	2
5151810TFT4	10	18	16 x 30	20	.012	.030	.324	302	2
5151812TFT4	12	18	16 x 30	20	.012	.030	.355	357	2
5151815TFT4	15	18	16 x 30	20	.012	.030	.388	460	2
5151816TFT4	16	18	16 x 30	20	.012	.030	.393	461	2
5151819TFT4	19	18	16 x 30	20	.012	.030	.431	560	2
5151825TFT4	25	18	16 x 30	20	.012	.035	.486	701	2
5151837TFT4	37	18	16 x 30	20	.012	.050	.605	1,054	2
5151651TFT4	2	16	26 x 30	18	.015	.023	.236	147	Black/Red
5151603TFT4	3	16	26 x 30	18	.015	.023	.250	180	1
5151604TFT4	4	16	26 x 30	18	.015	.023	.274	203	1

*Stranded **bare** copper conductors and special packaging and colours available upon request.
Aluminum or **Steel** Interlock Armour and Jacket available upon request.

The above data values are subject to change, please contact Electro Cables at sales@electrocables.com for verification of the above numbers to current manufacturing data values for your requirements or order.

This web site was last modified on Nov 27, 2015 , QMS registered to ISO 9001, Rev.60 All Rights Reserved.