

Plenum Shielded Multi-Conductor FT-6 300 Volts



1-888-Electro
Fax 613-394-4101
 SALES@ELECTROCABLES.COM

Stranded Tinned Copper Conductors*
 PVC Insulation, 100% Aluminum Foil Shield
 Stranded Tinned Copper Drain, Grey PVC Jacket FT-6
 75° C, 300 Volts

Contact sales@electrocables.com for approval info

[Home](#)
[Electronic & Electrical Index](#)
[Search](#)
[Previous](#) [Next](#)
[Colour Code: ECI Chart 1](#)

ECI Catalogue Number	Conductor No.	Conductor AWG Size	Conductor Stranding	Drain AWG Size	Wall Thickness Insulation (inches)	Wall Thickness Jacket (inches)	Nominal O.D. (inches)	Total Weight (lbs/km)	Colour Code
5152202TPV6	2	22	7 x 30	24	.008	.016	.122	35	ECI Chart 1
5152203TPV6	3	22	7 x 30	24	.008	.016	.129	45	1
5152204TPV6	4	22	7 x 30	24	.008	.016	.140	56	1
5152205TPV6	5	22	7 x 30	24	.008	.016	.147	67	1
5152207TPV6	7	22	7 x 30	24	.008	.016	.168	89	1
5152209TPV6	9	22	7 x 30	24	.008	.016	.186	112	1
5152002TPV6	2	20	7 x 28	24	.008	.016	.142	50	1
5151802TPV6	2	18	7 x 26	24	.008	.016	.162	66	1
5151803TPV6	3	18	7 x 26	24	.008	.016	.172	95	1
5151804TPV6	4	18	7 x 26	24	.008	.016	.188	119	1
5151805TPV6	5	18	7 x 26	24	.008	.016	.198	143	1
5151807TPV6	7	18	7 x 26	24	.008	.016	.229	195	1
5151809TPV6	9	18	7 x 26	24	.008	.016	.255	247	1
5151602TPV6	2	16	19 x 29	24	.008	.016	.180	96	1

*Stranded **bare** copper conductors and special packaging and colours available upon request.
Aluminum or **Steel** Interlock Armour and Jacket available upon request.

The above data values are subject to change, please contact Electro Cables at sales@electrocables.com for verification of the above numbers to current manufacturing data values for your requirements or order.

This web site was last modified on Nov 27, 2015 , QMS registered to ISO 9001, Rev.60 All Rights Reserved.