

Shielded Multi-Conductor FT-4



1-888-Electro
Fax 613-394-4101
SALES@ELECTROCABLES.COM

Stranded Tinned Copper Conductors*
SR-PVC Insulation, 100% Aluminum Foil Shield
Stranded Tinned Copper Drain, Grey PVC Jacket FT-4
-20° C to 105° C, Contact sales@electrocables.com for approval info

[Home](#)
[Electronic & Electrical Index](#)
[Search](#)
[Previous](#) [Next](#)
[Colour Code: ECI Chart 1](#)

| ECI Catalogue Number | Conductor | | | Drain AWG Size | Wall Thickness | | Nominal O.D. (inches) | Total Weight (lbs/km) | Colour Code |
|----------------------------|-----------|------|-----------|----------------------|------------------------|--------------------|-----------------------------|-----------------------------|-------------|
| | No. | Size | Stranding | | Insulation (inches) | Jacket (inches) | | | |
| 5152403TFT4 | 3 | 24 | 7 x 32 | 24 | .010 | .020 | .137 | 51 | ECI Chart 1 |
| 5152404TFT4 | 4 | 24 | 7 x 32 | 24 | .010 | .020 | .148 | 60 | 1 |
| 5152405TFT4 | 5 | 24 | 7 x 32 | 24 | .010 | .020 | .155 | 68 | 1 |
| 5152406TFT4 | 6 | 24 | 7 x 32 | 24 | .010 | .023 | .169 | 80 | 1 |
| 5152407TFT4 | 7 | 24 | 7 x 32 | 24 | .010 | .023 | .187 | 90 | 1 |
| 5152408TFT4 | 8 | 24 | 7 x 32 | 24 | .010 | .023 | .196 | 113 | 1 |
| 5152409TFT4 | 9 | 24 | 7 x 32 | 24 | .010 | .023 | .205 | 127 | 1 |
| 5152410TFT4 | 10 | 24 | 7 x 32 | 24 | .010 | .023 | .214 | 133 | 1 |
| 5152412TFT4 | 12 | 24 | 7 x 32 | 24 | .010 | .023 | .229 | 153 | 2 |
| 5152415TFT4 | 15 | 24 | 7 x 32 | 24 | .010 | .023 | .250 | 180 | 2 |
| 5152420TFT4 | 20 | 24 | 7 x 32 | 24 | .010 | .023 | .280 | 220 | 2 |
| 5152425TFT4 | 25 | 24 | 7 x 32 | 24 | .010 | .030 | .321 | 273 | 2 |
| 5152430TFT4 | 30 | 24 | 7 x 32 | 24 | .010 | .030 | .345 | 313 | 2 |
| 5152440TFT4 | 40 | 24 | 7 x 32 | 24 | .010 | .030 | .388 | 400 | 2 |
| 5152450TFT4 | 50 | 24 | 7 x 32 | 24 | .010 | .035 | .480 | 476 | 2 |
| 5152251TFT4 | 2 | 22 | 7 x 30 | 24 | .010 | .020 | .142 | 51 | Black/Red |
| 5152203TFT4 | 3 | 22 | 7 x 30 | 24 | .010 | .020 | .150 | 63 | 1 |
| 5152204TFT4 | 4 | 22 | 7 x 30 | 24 | .010 | .020 | .163 | 75 | 1 |
| 5152205TFT4 | 5 | 22 | 7 x 30 | 24 | .010 | .023 | .182 | 100 | 1 |
| 5152206TFT4 | 6 | 22 | 7 x 30 | 24 | .010 | .023 | .194 | 113 | 1 |
| 5152207TFT4 | 7 | 22 | 7 x 30 | 24 | .010 | .023 | .205 | 127 | 1 |
| 5152208TFT4 | 8 | 22 | 7 x 30 | 24 | .010 | .023 | .217 | 140 | 1 |

*Stranded **bare** copper conductors and special packaging and colours available upon request.
Aluminum or **Steel Interlock Armour** and Jacket available upon request.

The above data values are subject to change, please contact Electro Cables at sales@electrocables.com for verification of the above numbers to current manufacturing data values for your requirements or order.

This web site was last modified on Nov 27, 2015 , QMS registered to ISO 9001, Rev.60 All Rights Reserved.