

## Plenum Unshielded Multi-Conductor FT-6 300 Volts



1-888-Electro

Fax 613-394-4101

SALES@ELECTROCABLES.COM

Stranded Tinned Copper Conductors  
PVC Insulation, Grey PVC Jacket FT-6  
75° C, 300 Volts  
Contact [sales@electrocables.com](mailto:sales@electrocables.com) for approval info

[Home](#)

[Electronic & Electrical Index](#)

[Search](#)

[Previous](#)   [Next](#)

[Colour Code: ECI Chart 2](#)

ECI Catalogue Number	Conductor			Wall Thickness		Nominal O.D. (inches)	Total Weight (lbs/km)	Colour Code
	No.	AWG Size	Stranding	Insulation (inches)	Jacket (inches)			
6102251TPV6	2	22	7 x 30	.008	.016	.120	30	Black/Red
6102203TPV6	3	22	7 x 30	.008	.016	.127	40	Blk/Red/Green
6102204TPV6	4	22	7 x 30	.008	.016	.138	51	<a href="#">ECI Chart 1</a>
6102205TPV6	5	22	7 x 30	.008	.016	.145	62	1
6102206TPV6	6	22	7 x 30	.008	.016	.156	73	1
6102207TPV6	7	22	7 x 30	.008	.016	.166	84	1
6102208TPV6	8	22	7 x 30	.008	.016	.175	96	1
6102209TPV6	9	22	7 x 30	.008	.016	.184	107	1
6102210TPV6	10	22	7 x 30	.008	.016	.192	118	1
6101851TPV6	2	18	7 x 26	.008	.016	.160	60	Black/Red
6101803TPV6	3	18	7 x 26	.008	.016	.170	84	1
6101804TPV6	4	18	7 x 26	.008	.016	.186	108	1
6101805TPV6	5	18	7 x 26	.008	.016	.196	133	1
6101806TPV6	6	18	7 x 26	.008	.016	.212	160	1
6101807TPV6	7	18	7 x 26	.008	.016	.227	185	1
6101808TPV6	8	18	7 x 26	.008	.016	.240	211	1
6101809TPV6	9	18	7 x 26	.008	.016	.253	236	1
6101810TPV6	10	18	7 x 29	.008	.016	.265	261	1
6101602TPV6	2	16	19 x 29	.008	.016	.178	78	2
6101603TPV6	3	16	19 x 29	.008	.016	.189	110	2
6101604TPV6	4	16	19 x 29	.008	.016	.208	143	2
6101605TPV6	5	16	19 x 29	.008	.016	.220	175	2

\*Stranded *bare* copper conductors and special packaging available upon request.

*Aluminum* or *Steel* Interlock Armour and Jacket available upon request.

The above data values are subject to change, please contact Electro Cables at [sales@electrocables.com](mailto:sales@electrocables.com) for verification of the above numbers to current manufacturing data values for your requirements or order.

This web site was last modified on Nov 27, 2015 , QMS registered to ISO 9001, Rev.60 All Rights Reserved.