

Unshielded Multi-Conductor FT-4



1-888-Electro
Fax 613-394-4101
SALES @ ELECTROCABLES.COM

Stranded Tinned Copper Conductors*
SR-PVC Insulation, Grey PVC Jacket FT-4
-20° C to 105° C, Contact sales@electrocables.com for approval info

[Home](#)
[Electronic & Electrical Index](#)
[Search](#)
[Previous](#) [Next](#)
[Colour Code: ECI Chart 2](#)

ECI Catalogue Number	Conductor			Wall Thickness		Nominal O.D. (inches)	Total Weight (lbs/km)	Colour Code
	No.	AWG Size	Stranding	Insulation (inches)	Jacket (inches)			
6101602TFT4	2	16	26 x 30	.015	.023	.226	113	ECI Chart 2
6101603TFT4	3	16	26 x 30	.015	.023	.240	151	2
6101604TFT4	4	16	26 x 30	.015	.023	.263	190	2
6101605TFT4	5	16	26 x 30	.015	.023	.277	253	2
6101606TFT4	6	16	26 x 30	.015	.030	.314	279	2
6101607TFT4	7	16	26 x 30	.015	.030	.343	340	2
6101608TFT4	8	16	26 x 30	.015	.030	.353	370	2
6101609TFT4	9	16	26 x 30	.015	.030	.380	427	2
6101612TFT4	12	16	26 x 30	.015	.030	.430	553	2
6101615TFT4	15	16	26 x 30	.015	.035	.473	663	2
6101619TFT4	19	16	26 x 30	.015	.035	.524	821	2
6101625TFT4	25	16	26 x 30	.015	.050	.633	1,153	2

*Stranded **bare** copper conductors and special packaging and colours available upon request.
Aluminum or **Steel Interlock Armour** and Jacket available upon request.

The above data values are subject to change, please contact Electro Cables at sales@electrocables.com for verification of the above numbers to current manufacturing data values for your requirements or order.

This web site was last modified on Nov 27, 2015 , QMS registered to ISO 9001, Rev.60 All Rights Reserved.