

Unshielded Multi-Conductor FT-4



1-888-Electro

Fax 613-394-4101

SALES@ELECTROCABLES.COM

Stranded Tinned Copper Conductors*
 SR-PVC Insulation, Grey PVC Jacket FT-4
 -20° C to 105° C, Contact sales@electrocables.com for approval info

[Home](#)
[Electronic & Electrical Index](#)

[Search](#)

[Previous](#) [Next](#)

[Colour Code: ECI Chart 1](#)

| ECI Catalogue Number | Conductor | | | Wall Thickness | | Nominal O.D. (inches) | Total Weight (lbs/km) | Colour Code |
|----------------------------|-----------|------|-----------|------------------------|--------------------|-----------------------------|-----------------------------|-------------|
| | No. | Size | Stranding | Insulation (inches) | Jacket (inches) | | | |
| 6102007TFT4 | 7 | 20 | 7 x 28 | .010 | .023 | .225 | 153 | ECI Chart 1 |
| 6102009TFT4 | 9 | 20 | 7 x 28 | .010 | .023 | .249 | 187 | 1 |
| 6102010TFT4 | 10 | 20 | 7 x 28 | .010 | .023 | .264 | 208 | 1 |
| 6102012TFT4 | 12 | 20 | 7 x 28 | .010 | .023 | .279 | 233 | 1 |
| 6102015TFT4 | 15 | 20 | 7 x 28 | .010 | .030 | .306 | 305 | 2 |
| 6102019TFT4 | 19 | 20 | 7 x 28 | .010 | .030 | .338 | 374 | 2 |
| 6102025TFT4 | 25 | 20 | 7 x 28 | .010 | .030 | .380 | 478 | 2 |
| 6101851TFT4 | 2 | 18 | 16 x 30 | .012 | .020 | .195 | 87 | Black/Red |
| 6101803TFT4 | 3 | 18 | 16 x 30 | .012 | .023 | .207 | 113 | 1 |
| 6101804TFT4 | 4 | 18 | 16 x 30 | .012 | .023 | .226 | 147 | 1 |
| 6101805TFT4 | 5 | 18 | 16 x 30 | .012 | .023 | .237 | 167 | 1 |
| 6101806TFT4 | 6 | 18 | 16 x 30 | .012 | .023 | .255 | 193 | 1 |
| 6101807TFT4 | 7 | 18 | 16 x 30 | .012 | .023 | .271 | 220 | 1 |
| 6101808TFT4 | 8 | 18 | 16 x 30 | .012 | .023 | .286 | 246 | 1 |
| 6101809TFT4 | 9 | 18 | 16 x 30 | .012 | .023 | .300 | 273 | 1 |
| 6101812TFT4 | 12 | 18 | 16 x 30 | .012 | .030 | .353 | 360 | 2 |
| 6101815TFT4 | 15 | 18 | 16 x 30 | .012 | .030 | .386 | 440 | 2 |
| 6101819TFT4 | 19 | 18 | 16 x 30 | .012 | .030 | .429 | 547 | 2 |
| 6101825TFT4 | 25 | 18 | 16 x 30 | .012 | .035 | .485 | 686 | 2 |
| 6101830TFT4 | 30 | 18 | 16 x 30 | .012 | .035 | .524 | 809 | 2 |
| 6101840TFT4 | 40 | 18 | 16 x 30 | .012 | .050 | .633 | 1147 | 2 |

*Stranded **bare** copper conductors and special packaging and colours available upon request.
Aluminum or **Steel Interlock Armour** and Jacket available upon request.

The above data values are subject to change, please contact Electro Cables at sales@electrocables.com for verification of the above numbers to current manufacturing data values for your requirements or order.

This web site was last modified on Nov 27, 2015 , QMS registered to ISO 9001, Rev.60 All Rights Reserved.