

Shielded Multi-Conductor FT-4



1-888-Electro
Fax 613-394-4101
SALES@ELECTROCABLES.COM

Stranded Tinned Copper Conductors*
Polyethylene Insulation, 100% Aluminum Foil Shield
Stranded Tinned Copper Drain, Grey PVC Jacket FT-4
-20° C to 75 ° C, Contact sales@electrocables.com for approval info

[Home](#)
[Electronic & Electrical Index](#)
[Search](#)
[Previous](#) [Next](#)
[Colour Code: ECI Chart 1](#)

ECI Catalogue Number	Conductor		Drain AWG Size	Wall Thickness Insulation (inches)	Jacket (inches)	Nominal O.D. (inches)	Total Weight (lbs/km)	Colour Code
	No.	Size Stranding						
5032402TFT4	2	24 7 x 32	24	.015	.020	.150	46	ECI Chart 1
5032202TFT4	2	22 7 x 30	24	.015	.020	.162	57	1
5032203TFT4	3	22 7 x 30	24	.015	.023	.184	73	1
5032204TFT4	4	22 7 x 30	24	.015	.023	.200	93	1
5032205TFT4	5	22 7 x 30	24	.015	.023	.202	99	1
5032002TFT4	2	20 7 x 28	22	.015	.023	.187	73	1
5032003TFT4	3	20 7 x 28	22	.015	.023	.197	93	1
5032004TFT4	4	20 7 x 28	22	.015	.023	.216	133	1
5031802TFT4	2	18 16 x 30	20	.015	.023	.210	100	1
5031803TFT4	3	18 16 x 30	20	.015	.023	.222	127	1
5031804TFT4	4	18 16 x 30	20	.015	.023	.242	153	1
5031602TFT4	2	16 26 x 30	18	.015	.023	.236	133	1
5031603TFT4	3	16 26 x 30	18	.015	.023	.242	168	1
5031604TFT4	4	16 26 x 30	18	.015	.023	.265	207	1
5031402TFT4	2	14 41 x 30	16	.030	.030	.338	233	1
5031403TFT4	3	14 41 x 30	16	.030	.030	.359	300	1
5031404TFT4	4	14 41 x 30	16	.030	.030	.394	373	1
5031202TFT4	2	12 65 x 30	14	.030	.030	.376	312	1
5031203TFT4	3	12 65 x 30	14	.030	.030	.400	412	1
5031204TFT4	4	12 65 x 30	14	.030	.030	.440	520	1

*Stranded **bare** copper conductors and special packaging and colours available upon request.
Aluminum or **Steel Interlock Armour** and Jacket available upon request.

The above data values are subject to change, please contact Electro Cables at sales@electrocables.com for verification of the above numbers to current manufacturing data values for your requirements or order.

This web site was last modified on Nov 27, 2015 , QMS registered to ISO 9001, Rev.60 All Rights Reserved.