

Unshielded Multi-Conductor FT-4



1-888-Electro
Fax 613-394-4101
SALES @ ELECTROCABLES.COM

Stranded Tinned Copper Conductors*
SR-PVC Insulation, Grey PVC Jacket FT-4
-20° C to 105° C
Contact sales@electrocables.com for approval info

[Home](#)
[Electronic & Electrical Index](#)
[Search](#)
[Next](#)
[Colour Code: ECI Chart 1](#)

ECI Catalogue Number	Conductor			Wall Thickness		Nominal O.D. (inches)	Total Weight (lbs/km)	Colour Code
	No.	AWG Size	Stranding	Insulation (inches)	Jacket (inches)			
6102251TFT4	2	22	7 x 30	.010	.015	.131	40	Black/Red
6102203TFT4	3	22	7 x 30	.010	.015	.139	47	Blk/Red/Green
6102204TFT4	4	22	7 x 30	.010	.015	.152	60	ECI Chart 1
6102205TFT4	5	22	7 x 30	.010	.015	.160	73	1
6102206TFT4	6	22	7 x 30	.010	.023	.192	107	1
6102207TFT4	7	22	7 x 30	.010	.023	.203	113	1
6102208TFT4	8	22	7 x 30	.010	.023	.215	127	1
6102209TFT4	9	22	7 x 30	.010	.023	.225	140	1
6102210TFT4	10	22	7 x 30	.010	.023	.234	153	1
6102212TFT4	12	22	7 x 30	.010	.023	.251	180	1
6102215TFT4	15	22	7 x 30	.010	.023	.275	213	2
6102216TFT4	16	22	7 x 30	.010	.023	.285	226	2
6102218TFT4	18	22	7 x 30	.010	.023	.290	230	2
6102220TFT4	20	22	7 x 30	.010	.030	.323	286	2
6102225TFT4	25	22	7 x 30	.010	.030	.354	346	2
6102230TFT4	30	22	7 x 30	.010	.030	.381	413	2
6102240TFT4	40	22	7 x 30	.010	.030	.432	526	2
6102250TFT4	50	22	7 x 30	.010	.035	.493	640	2
6102051TFT4	2	20	7 x 28	.010	.015	.146	47	Black/Red
6102003TFT4	3	20	7 x 28	.010	.015	.154	60	1
6102004TFT4	4	20	7 x 28	.010	.023	.189	100	1
6102005TFT4	5	20	7 x 28	.010	.023	.197	113	1

*Stranded **bare** copper conductors and special packaging and colours available upon request.
Aluminum or **Steel Interlock Armour** and Jacket available upon request.

The above data values are subject to change, please contact Electro Cables at sales@electrocables.com for verification of the above numbers to current manufacturing data values for your requirements or order.

This web site was last modified on Nov 27, 2015 , QMS registered to ISO 9001, Rev.60 All Rights Reserved.