

EPIC® H-BE 2.5 machined contacts

For inserts and modules of the EPIC® rectangular connectors

The machined contacts for rectangular connectors are available as female and male pins with various cross-section dimensions.

Info

Choice of high quality gold or silver plated contacts



Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC000796

ETIM 5.0 Class-Description: Contact for industrial connectors

Classification ETIM 6:

ETIM 6.0 Class-ID: EC000796

ETIM 6.0 Class-Description: Contact for industrial connectors

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

EPIC® H-BE 2.5 machined contacts

Article number	Article description	Contact type	Conductor cross-section (mm ²)	Cross-section identification	Surface	Stripping length (mm)
Contacts						
11190000	H-BE 2.5 machined	male	0.5	-	Ag	7.4
11195000	H-BE 2.5 machined	female	0.5	-	Ag	7.4
11190100	H-BE 2.5 machined	male	0.75 - 1	1	Ag	7.4
11195100	H-BE 2.5 machined	female	0.75 - 1	1	Ag	7.4
11190200	H-BE 2.5 machined	male	1.5	2	Ag	7.4
11195200	H-BE 2.5 machined	female	1.5	2	Ag	7.4
11190300	H-BE 2.5 machined	male	2.5	3	Ag	7.4
11195300	H-BE 2.5 machined	female	2.5	3	Ag	7.4
11190400	H-BE 2.5 machined	male	4	-	Ag	7.4
11195400	H-BE 2.5 machined	female	4	-	Ag	7.4
Contacts						
11190301	H-BE 2.5 machined	male	0.14 - 0.37	2	Au	7.4
11190302	H-BE 2.5 machined	female	0.14 - 0.37	2	Au	7.4
11192000	H-BE 2.5 machined	male	0.5	-	Au	7.4
11197000	H-BE 2.5 machined	female	0.5	-	Au	7.4
11192100	H-BE 2.5 machined	male	0.75 - 1	1	Au	7.4
11197100	H-BE 2.5 machined	female	0.75 - 1	1	Au	7.4
11192200	H-BE 2.5 machined	male	1.5	2	Au	7.4
11197200	H-BE 2.5 machined	female	1.5	2	Au	7.4
11192300	H-BE 2.5 machined	Pin	2.5	3	Au	7.4
11197300	H-BE 2.5 machined	female	2.5	3	Au	7.4

Last Update (03.08.2018)

©2018 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

 You can find the current technical data in the corresponding data sheet:
 PN 0456 / 02_03_16