
REV.	DESCRIPTION	DATE
0	Initial Release.	01/16/2006
1	Increase Overall Diameter dimension	01/27/2006
2	Change shield from .003" Fusible to .0015" non fusible	02/02/06

General Properties:



Col	Color Code			
1	Natural			
2	Natural			
3	RD			
4	BK			
Jacket	BK			

Cable Construction:

Primaries 1 & 2 (Siamese)	Description	Dimensions	
1. Conductor:	22 AWG 7/30 Copper, (1) bare copper (1) tin plated copper	0.030 " $\pm .001$ " [0.76mm]	
2. Insulation:	Cellular EXRAD 150FX (reference 25 mil [0.64mm] wall)	0.144" x 0.080" nominal	
Extrusion:	(2) Conductors extruded with Siamese profile	[3.65 mm x 2.03 mm]	
Primaries 3 & 4 (Power)			

Conductor: 22 AWG 7/30 Bare Copper 0.030" $\pm .001$ " [0.76mm] EXRAD 150UT Solid, 10 mil [.25mm] wall nominal 0.050" $\pm .002$ " [1.27mm] 4. Insulation: Drain: 22 AWG 7/30 Bare Copper 0.030" $\pm .001$ " [0.76mm]

Overall Cable: Siamese foamed pair, (2) solid singles, fillers and drain wire pulled

in as drawing shows and twisted

Lay Length: 3" to 4"

Filler: (4) Water absorbent yarn 0.153" ± .005" [3.89mm] 1.5 mil Aluminum/ Mylar, Shield 20% min overlap 7. Shield: 0.157" $\pm .005$ " [4.00mm] EXRAD 150FX, OD run to OD (reference 23.5 mil [.60mm] wall) 8. Jacket: 0.200" $\pm .005$ " [5.08mm]

Pressure extruded for roundness

Technical Details (*Foamed Siamese Pair Only):

Voltage Rating: 300 V (all conductors) Temperature Rating: -40 °C to 125 °C

Impedance: Single Ended *75 +/- 5 Ohms - conductor to ground (drain/or return grounded)

> Differential *95 Ohms +/- 10% - conductor to conductor (drain grounded) @ 10 - 20 MHz

CHAMPLAIN CABLE 175 HERCULES DRIVE COLCHESTER, VT 05446 802-654-4200	CAMERA CABLE 22 AWG Siamese Signal + Power and Ground With Water Absorbent Yarn						
	DRN.		DATE				
UNLESS OTHERWISE SPECIFIED,	Ken Scherzinger		01/16/2006				
DIMENSIONS AND TOLERANCES ARE IN INCHES	CKD.		DATE				
DO NOT SCALE THIS DRAWING	SIZE	PART NUMBER	DOCUMENT NUMBER				
	Α	15-07482-001	128	91			
The information on this drawing is the proprietary pro in w	PAGE 1 of 1						