



Ferrules, Non-Insulated (continued)

Type F

Part Number	Wire Size		Figure Dimensions						Wire Strip Length		Recommended Installation Tool	Std. Pkg. Qty.
	AWG	mm ²	L		ID		OD		In.	mm		
F83-12-D‡	8 AWG	10.0	0.47	12.0	0.18	4.5	0.19	4.9	15/32	12.0	‡CT-1003, ‡CT-1004, CT-1123, CT-1104	500
F83-15-D‡			0.59	15.0	0.18	4.5	0.19	4.9	19/32	15.0		500
F83-18-D‡			0.71	18.0	0.18	4.5	0.19	4.9	23/32	18.0		500
F83-20-D‡			0.79	20.0	0.18	4.5	0.19	4.9	25/32	20.0		500
F83-25-D‡			0.98	25.0	0.18	4.5	0.19	4.9	31/32	25.0		500
F84-12-TL‡	6 AWG	16.0	0.47	12.0	0.23	5.8	0.24	6.2	15/32	12.0	‡CT-1004, CT-1104	250
F84-15-TL‡			0.59	15.0	0.23	5.8	0.24	6.2	19/32	15.0		250
F84-18-TL‡			0.71	18.0	0.23	5.8	0.24	6.2	23/32	18.0		250
F84-20-TL‡			0.79	20.0	0.23	5.8	0.24	6.2	25/32	20.0		250
F84-25-TL‡			0.98	25.0	0.23	5.8	0.24	6.2	31/32	25.0		250
F84-32-TL‡	1.26	32.0	0.23	5.8	0.24	6.2	1 1/4	32.0	250			
F85-12-C	4 AWG	25.0	0.47	12.0	0.29	7.3	0.30	7.7	15/32	12.0	CT-1005	100
F85-15-C			0.59	15.0	0.29	7.3	0.30	7.7	19/32	15.0		100
F85-18-C			0.71	18.0	0.29	7.3	0.30	7.7	23/32	18.0		100
F85-25-C			0.98	25.0	0.29	7.3	0.30	7.7	31/32	25.0		100
F85-32-C			1.26	32.0	0.29	7.3	0.30	7.7	1 1/4	32.0		100
F86-18-C	2 AWG	35.0	0.71	18.0	0.33	8.3	0.34	8.7	23/32	18.0	CT-1005	100
F86-20-C			0.79	20.0	0.33	8.3	0.34	8.7	25/32	20.0		100
F86-25-C			0.98	25.0	0.33	8.3	0.34	8.7	31/32	25.0		100
F86-32-C			1.26	32.0	0.33	8.3	0.34	8.7	1 1/4	32.0		100
F87-18-C			0.71	18.0	0.41	10.3	0.43	10.9	23/32	18.0		100
F87-22-C	1 AWG-1/0	50.0	0.87	22.0	0.41	10.3	0.43	10.9	7/8	22.0	CT-1006, **CD-2001-F87	100
F87-25-C			0.98	25.0	0.41	10.3	0.43	10.9	31/32	25.0		100
F87-32-C			1.26	32.0	0.41	10.3	0.43	10.9	1 1/4	32.0		100
F89-25-L*	2/0	70.0	0.98	25.0	0.49	12.5	0.52	13.3	31/32	25.0	**CD-2001-F89	50
F89-32-L*			1.26	32.0	0.49	12.5	0.52	13.3	1 1/4	32.0		50
F90-25-L*	3/0	95.0	0.98	25.0	0.57	14.5	0.60	15.3	31/32	25.0	**CD-2001-F90	50
F90-30-L*			1.18	30.0	0.57	14.5	0.60	15.3	13/16	30.0		50
F90-32-L*			1.26	32.0	0.57	14.5	0.60	15.3	1 1/4	32.0		50
F91-32-L*	4/0-250 kcmil	120.0	1.26	32.0	0.65	16.5	0.69	16.5	1 1/4	32.0	**CD-2001-F91	50
F91-40-L*			1.57	40.0	0.65	16.5	.069	16.5	1 19/32	40.0		50
F92-32-L*	300 kcmil	150	1.26	32.0	0.73	18.5	0.77	19.5	1 1/4	32.0	**CD-2001-F92	50
F92-38-L*			1.50	38.0	0.73	18.5	0.77	19.5	1 1/2	38.0		50
F93-32-Q*	350 kcmil	185	1.26	32.0	0.79	20.0	0.83	21.2	1 1/4	32.0	**CD-2001-F93	25
F93-40-Q*			1.57	40.0	0.79	20.0	0.83	21.2	1 19/32	40.0		25
F94-40-Q*	500 kcmil	240	1.57	40.0	0.90	22.8	0.94	24.0	1 19/32	40.0	**CD-2001-F94	25

*Not UL listed, UL486F scope is 20 - 1/0 AWG only

+UL listed with 20 AWG only

‡Tool/Part is not a UL listed Combination. For crimping tool information see www.panduit.com/tools.

**Dies used with CT-3001 or CT-3001/E tool

B1.
Cable
Ties

B2.
Cable
Accessories

B3.
Stainless
Steel Cable
Ties &
Accessories

C1.
Wiring
Duct

C2.
Abrasion
Protection

C3.
Cable
Management

D1.
Terminals

D2.
Power
Connectors

D3.
Grounding
Connectors

E1.
Labeling
Systems

E2.
Labels

E3.
Pre-Printed
&
Write-On
Markers

E4.
Permanent
Identification

E5.
Industrial
Safety
Solutions

F.
Keystone
Cabling
Systems


G.
Part
Number
Index



Ferrules, Non-Insulated

Type F

- Designed with a seamless barrel to contain loose wire strands for superior terminations
- Eases insertion of wire into terminal block
- Meets DIN standards for wire containment
- Suitable for limited space panel applications
- Multiple pin lengths available for a variety of terminal blocks



Part Number	Wire Size		Figure Dimensions						Wire Strip Length		Recommended Installation Tool	Std. Pkg. Qty.			
			L		ID		OD		In.	mm					
	AWG	mm ²	In.	mm	In.	mm	In.	mm							
F73-5-M*	24 AWG	0.25	0.20	5.0	0.03	0.80	0.04	1.1	7/32	5.0	CT-1002, CT-1123	1000			
F73-7-M*			0.28	7.0	0.03	0.80	0.04	1.1	9/32	7.0		1000			
F74-5-M*	24 – 22 AWG	0.34	0.20	5.0	0.04	0.90	0.05	1.2	7/32	5.0		1000			
F74-7-M*			0.28	7.0	0.04	0.90	0.05	1.2	9/32	7.0		1000			
F75-6-M+	22 – 20 AWG	0.50	0.24	6.0	0.04	1.0	0.05	1.3	1/4	6.0	CT-1002, CT-1003, CT-1123	1000			
F75-8-M+			0.31	8.0	0.04	1.0	0.05	1.3	5/16	8.0		1000			
F75-10-M+			0.39	10.0	0.04	1.0	0.05	1.3	13/32	10.0		1000			
F76-6-M	18 AWG	0.75	0.24	6.0	0.05	1.2	0.06	1.5	1/4	6.0		1000			
F76-8-M			0.31	8.0	0.05	1.2	0.06	1.5	5/16	8.0		1000			
F76-10-M			0.39	10.0	0.05	1.2	0.06	1.5	13/32	10.0		1000			
F76-12-M			0.47	12.0	0.05	1.2	0.06	1.5	15/32	12.0	1000				
F77-6-M	16 AWG	1.0	0.24	6.0	0.06	1.4	0.07	1.7	1/4	6.0	CT-1002, CT-1003, CT-1123	1000			
F77-7-M			0.28	7.0	0.06	1.4	0.07	1.7	9/32	7.0		1000			
F77-8-M			0.31	8.0	0.06	1.4	0.07	1.7	5/16	8.0		1000			
F77-10-M			0.39	10.0	0.06	1.4	0.07	1.7	13/32	10.0		1000			
F77-12-M			0.47	12.0	0.06	1.4	0.07	1.7	15/32	12.0		1000			
F78-7-M	14 AWG	2.5	0.28	7.0	0.07	1.7	0.08	2.0	9/32	7.0		CT-1002, CT-1003, CT-1123	1000		
F78-8-M			0.31	8.0	0.07	1.7	0.08	2.0	5/16	8.0			1000		
F78-10-M			0.39	10.0	0.07	1.7	0.08	2.0	13/32	10.0			1000		
F78-12-M			0.47	12.0	0.07	1.7	0.08	2.0	15/32	12.0			1000		
F78-15-M			0.59	15.0	0.07	1.7	0.08	2.0	19/32	15.0			1000		
F78-18-M			0.71	18.0	0.07	1.7	0.08	2.0	23/32	18.0	1000				
F78-20-M			0.79	20.0	0.07	1.7	0.08	2.0	25/32	20.0	1000				
F80-7-M			12 AWG	4.0	0.28	7.0	0.09	2.2	0.10	2.5	9/32		7.0	CT-1002, CT-1003, CT-1123	1000
F80-8-M	0.31	8.0			0.09	2.2	0.10	2.5	5/16	8.0	1000				
F80-10-M	0.39	10.0			0.09	2.2	0.10	2.5	13/32	10.0	1000				
F80-12-M	0.47	12.0			0.09	2.2	0.10	2.5	15/32	12.0	1000				
F80-15-M	0.59	15.0			0.09	2.2	0.10	2.5	19/32	15.0	1000				
F80-18-M	0.71	18.0			0.09	2.2	0.10	2.5	23/32	18.0	1000				
F80-20-M	0.79	20.0			0.09	2.2	0.10	2.5	25/32	20.0	1000				
F81-9-M	10 AWG	6.0			0.35	9.0	0.11	2.8	0.13	3.2	11/32		8.0		CT-1002, ‡CT-1003, CT-1123
F81-10-M			0.39	10.0	0.11	2.8	0.13	3.2	13/32	10.0	1000				
F81-12-M			0.47	12.0	0.11	2.8	0.13	3.2	15/32	12.0	1000				
F81-15-M			0.59	15.0	0.11	2.8	0.13	3.2	19/32	15.0	1000				
F81-18-M			0.71	18.0	0.11	2.8	0.13	3.2	23/32	18.0	1000				
F81-20-M			0.79	20.0	0.11	2.8	0.13	3.2	25/32	20.0	1000				
F82-10-M‡			8 AWG	10.0	0.39	10.0	0.14	3.5	0.15	3.9	13/32	10.0	1000		
F82-12-M‡					0.47	12.0	0.14	3.5	0.15	3.9	15/32	12.0	1000		
F82-15-M‡	0.59	15.0			0.14	3.5	0.15	3.9	19/32	15.0	1000				
F82-18-M‡	0.71	18.0			0.14	3.5	0.15	3.9	23/32	18.0	1000				
F82-20-M‡			0.79	20.0	0.14	3.5	0.15	3.9	25/32	20.0	1000				

*Not UL listed, UL 486F scope is 20 - 1/0 AWG only

+UL listed with 20 AWG only

‡Tool/Part is not a UL listed Combination. For crimping tool information see www.panduit.com/tools.