

1. CONDUCTOR:

- 1.1 Size and Material: 18 16/30 AWG tin-plated copper wire.
- 1.2 O.D.: .045" nom.

2. INSULATION:

- 2.1 Extruded flame retardant silicone rubber.
- 2.2 Marking on the insulation: as per UL and CSA Standards.
- 2.3 O.D.: .145" nom.
- 2.4 Color: as per order (replace X in the part number and the description by 0-9 color code).
- 2.5 Talc powder applied on the insulation.

3. PERFORMANCE:




- 3.1 Voltage rating: 20 KVDC
- 3.2 Temperature rating: 150°C

4. REFERENCE:

- 4.1 UL Subject 758 (AWM), Style 3239.
- 4.2 CSA Standard C22.2 No. 127-95 (Equipment/Lead Wire), Type TV-20.

CUSTOMER APPROVAL

Sign: _____
 Date: _____

Engineering Change Notice No.								 <p>This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.</p>	Done:		 <p>1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourintl.com</p>				
									Date: January 15, 2004						
									Verified:		Description: XSF50Z1816/30-X				
									Date: January 15, 2004						
UNCONTROLLED DOCUMENT A later revision of this specification may exist.								 <p>A member of The Marmon Group of companies</p>		Size: A	Scale: ---	Page: 1 of 1	Code Ident. No: 57104	Specification No.: F00190-X	Rev. ---