

**1. CONDUCTOR:**

- 1.1 Size and Material: 22 7/30 AWG nickel-plated copper wire.
- 1.2 O.D.: .030" nom.

**2. INSULATION:**

- 2.1 Extruded PFA.
- 2.2 Marking on the insulation: not required as per UL Standard.
- 2.3 O.D.: .086" nom.
- 2.4 Color: as per order (replace X in the part number and the description by 0-9 color code).

**3. PERFORMANCE:**

- 3.1 Voltage rating: 25 KVDC
- 3.2 Temperature rating: 250°C




**4. REFERENCE:**

- 4.1 UL subject 758 (AWM), Style 1911.

**CUSTOMER APPROVAL**

Sign: \_\_\_\_\_

Date: \_\_\_\_\_

Engineering Change Notice No.								 <p>This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.</p>		Done: <i>Pierre Garand</i>		 <p>1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourintl.com</p>				
										Date: January 19, 2005						
										Verified:		Description: <b>XPA28N227/30-X</b>				
										Date:		Code Ident. No: <b>57104</b>		Specification No.: <b>F04210-X</b>		Rev. <b>---</b>
<b>UNCONTROLLED DOCUMENT</b> A later revision of this specification may exist.								 <p>A member of The Marmon Group of companies</p>		Size: <b>A</b>	Scale: <b>---</b>	Page: <b>1 of 1</b>				