PRODUCT SPECIFICATION

REV DESCRIPTION DATE **ECN** 8/24/2016 Е Corrected conductor description.


Parent Number: F06078-

Description: 6 7x19/27 TC AWM 3196 UL SIS CL 1251

AWM I A/B

DIAMETER: 0.338

TOLERANCE + : 0.010



Stranding: 7x19/27 TC LHL

Style: UL: SIS or AWM 3196 or 3237 CSA: CL1251 or AWM I A/B

MIN AVG WALL: 0.060

MINIMUM WALL: 0.054

Insulation: XLPE

<u>Print Legend:</u> 6 AWG (13.30mm2) E30117 (PLANT ID CODE) (UL) SIS 90C 600V AND AWM 3196 125C 600V OR 3237 105C 1000V -- 156205 CSA CL1251 125C 600V OR AWM I A/B 125C 600V FT2 -- MADE IN USA

Voltage: 600V, AWM 3237 = 1,000V

Temperature: 125C, SIS = 90C, 3237 = 105C

Notes: 1. Min Temp = -40C

This product complies with European Directive 2011/65/EU (RoHS 2)

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

Customer Approval:	
Customer Part Nbr(s):	
Approved By:	Date:
Title ·	Company Name:

Southwire'

1115 W. North Street Bremen, IN 46506

Phone: 1-574-546-5115