PRODUCT SPECIFICATION

DATEREVECNDESCRIPTION11/16/2015BUpdated temperature ratings.


Parent Number: F06119-

Description: 6 133/.0142 TC SGT Marine per J1127/J378

105C Indent Print

DIAMETER: 0.301

TOLERANCE ±: 0.010



NOM WALL: 0.060

MINIMUM WALL: 0.042

Stranding: 133/.0142 TC LHL

Style: SGT Marine per SAE J1127/J378

Insulation: PVC

Print Legend: CF 6 AWG MARINE SAE J-1127 AND J-378 105°C 60V DC

Voltage: Per SAE J 1127 this product is intended for use at a nominal system voltage of 60 Volts DC or less in surface vehicle electrical

systems.

Temperature: -40C to +105C

Notes:

This product complies with European Directive 2015/863 -- RoHS 3.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

<u>Customer Approval:</u>		
Customer Part Nbr(s):		
Approved By:	Date:	
Title:	Company Name:	

Southwire

Copperfield®

1115 W. North Street Bremen, IN 46506 Phone: 1-574-546-5115