## **PRODUCT SPECIFICATION**

REV DESCRIPTION DATE **ECN** 3/15/2016 ADDED NOTE 1.


Parent Number: F08034-

Description: 8 19/UL Combo BC AWM 3195 UL SIS CL

1251 AWM I A/B

DIAMETER: 0.246

*TOLERANCE* + : 0.005



Stranding: 19/UL Combo BC LHL

Style: UL: AWM 3195 UL SIS CSA: CL1251 or AWM I A/B

MIN AVG WALL: 0.045

MINIMUM WALL: 0.040

**Insulation:** XLPE

Print Legend: 8 AWG (8.37mm2) E30117 (PLANT ID CODE) (UL) SIS 600V AND AWM 3195 600V OR 3237 1000V -- 156205 CSA CL1251 125C 600V OR AWM

I A/B 125C 600V FT2 -- MADE IN USA

Voltage: 600V

Temperature: 125C

*Notes:* 1. Separator is used between the copper conductor and insulation.

This product complies with European Directive 2015/863 -- RoHS 3.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

<u>Customer Approval:</u>		
Customer Part Nbr(s):		
Approved By:	Date:	
Title:	Company Name:	

Southwire'

1115 W. North Street Bremen, IN 46506

Phone: 1-574-546-5115