## **PRODUCT SPECIFICATION**


DATEREVECNDESCRIPTION11/22/2004A7012SPECIFICATION CREATED

Parent Number: F12011-

Description: 12 19/25 TC GPT Marine per SAE J1128/J378

**DIAMETER:** 0.142

*TOLERANCE* ± : 0.003



**NOM WALL:** 0.026

MINIMUM WALL: 0.018

Stranding: 19/25 TC LHL

Style: GPT Marine per SAE J378/J1128

**Insulation:** PVC

Print Legend: CF 12 AWG MARINE SAE J-378 AND J-1128 105C 60V DC

Voltage: Per SAE J 1128 this product is intended for use at a nominal system voltage of 60 Volts DC or less in surface vehicle electrical

systems.

Temperature: 105C

Notes:

This product complies with European Directive 2015/863 -- RoHS 3.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

Customer Approval:

Customer Part Nbr(s):

Approved By:

Title:

Company Name:

Southwire

Copperfield®

1115 W. North Street Bremen, IN 46506 Phone: 1-574-546-5115