

DATE	REV	ECN	DESCRIPTION
7/2/2010	F	#13004	SPECIFICATION UPDATED

PRODUCT SPECIFICATION

Parent Number: F14052-

Description: 14 7/.0242 TC AWM 3071/3231 SF-2 SEW-2
Braided Silicone

DIAMETER: 0.132
TOLERANCE ± : 0.003



MIN AVG WALL: 0.030
MINIMUM WALL: 0.027

Stranding: 7/.0242 TC LHL

Style: UL: AWM 3071/3231 SF-2 CSA: SEW-2

Insulation: Braided Silicone

Print Legend: 14 AWG (2.08mm²) E30071 (PLANT ID CODE) (UL) TYPE SF-2 OR AWM 3071/3231 200C 600V -- 156205 CSA SEW-2 200C 600V FT1

Voltage: 600V

Temperature: 200C

- Notes:**
1. Diameter shown is OD under braid.
 2. OD over the braid is approximately 0.143"

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

Customer Approval:

Customer Part Nbr(s): _____

Approved By: _____ **Date:** _____

Title: _____ **Company Name:** _____



Southwire
Copperfield[®]
1115 W. North Street
Bremen, IN 46506
Phone: 1-574-546-5115