PRODUCT SPECIFICATION


DATEREVECNDESCRIPTION7/25/2011B#13832SPECIFICATION UPDATED

Parent Number: F18415-

Description: 18 16/30 TC AWM 3199 CL 1252 OD 0.080"

DIAMETER: 0.080

TOLERANCE ± : 0.003



MIN AVG WALL: 0.015

MINIMUM WALL: 0.013

Stranding: 16/30 TC LHL

Style: UL: AWM 3199 CSA: CL 1252

Insulation: XLPE

Print Legend: 18 AWG (0.823mm2) E57498 (PLANT ID CODE) (AWM LOGO) AWM 3199 105C 300V -- 156205 CSA CL1252 125C 300V

Voltage: 300V

Temperature: <u>UL=105C, CSA=125C</u>

Notes:

This product complies with European Directive 2011/65/EU (RoHS 2)

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

Customer Approval:		
Customer Part Nbr(s):		
Approved By:	Date:	
Title:	Company Name:	

Southwire

Copperfield

1115 W. North Street Bremen, IN 46506 Phone: 1-574-546-5115