DESCRIPTION DATE REV **ECN** 04/29/14 Α SPECIFICATION CREATED **PRODUCT SPECIFICATION Parent Number:** F18486-**DIAMETER:** 0.110 Description: 18 16/30 TC UL XFF or AWM 3321 CL1503 or AWMIA **TOLERANCE** + : 0.003 Stranding: 16/30 TC LHL **MIN AVG WALL:** 0.030 Style: UL: UL XFF or AWM 3321 CSA: CL1503 or AWM I A MINIMUM WALL: 0.027 Insulation: XLPE Print Legend: 18 AWG (0.823mm2) E30071 (PLANT ID CODE) (UL) XFF 150C 300V OR AWM 3321 150C 600V -- 156016 CSA CL1503 150C 600V OR AWM IA 150C 600V FT1 Voltage: UL=600Vac 750Vdc, CSA=600V *Temperature:* <u>150C</u> Notes: This product complies with European Directive 2011/65/EU (RoHS 2) The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise. Southwire' This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC. Copperfield Customer Approval: Customer Part Nbr(s):_____ Approved By:_____ Date:_____ 1115 W. North Street Bremen, IN 46506 Title: Company Name: Phone: 1-574-546-5115