


DATE	REV	ECN	DESCRIPTION
9/14/2015	E		Updated low temp info.

**PRODUCT SPECIFICATION**

**Parent Number:** F20037-

**Description:** 20 10/30 TC MTW or AWM  
 1011/1015/1230/1335 or 1032 TEW or AWM I A/B  
**DIAMETER:** 0.099  
**TOLERANCE ± :** 0.003



**MIN AVG WALL:** 0.030  
**MINIMUM WALL:** 0.027

**Stranding:** 10/30 TC LHL

**Style:** UL: MTW or AWM 1011/1015/1230/1335 or 1032 CSA: TEW or AWM I A/B

**Insulation:** PVC

**Print Legend:** 20 AWG (0.519mm<sup>2</sup>) E51583 (PLANT ID CODE) (UL) MTW OR AWM 1011/1015/1230/1335 600V OR 1032 1000V MOISTURE RESISTANT VW-1 -- 156205 CSA TEW 105C 600V FT1 OR AWM I A/B 105C 600V FT-1

**Voltage:** 600V, 1032=1000V

**Temperature:** MTW: DRY=90C WET=60C, 1015=105C, 1230: DRY=105C WET=60C, 1011=80C, 1032=90C, 1335: DRY=90C WET=60C

- Notes:**
1. Min Temp: -40C
  2. CSA TEW: -30C

This product complies with European Directive 2011/65/EU (RoHS 2)

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

**Customer Approval:**

**Customer Part Nbr(s):** \_\_\_\_\_

**Approved By:** \_\_\_\_\_ **Date:** \_\_\_\_\_

**Title:** \_\_\_\_\_ **Company Name:** \_\_\_\_\_



**Southwire**  
**Copperfield**<sup>®</sup>  
 1115 W. North Street  
 Bremen, IN 46506  
 Phone: 1-574-546-5115