

DATE	REV	ECN	DESCRIPTION
4/28/2017	C		Added RoHS statement.

PRODUCT SPECIFICATION

Parent Number: F20123-

Description: 20 10/30 2% Nickel Plated AWM 3172 SEWF-2 Braided Silicone

DIAMETER: 0.096
TOLERANCE ± : 0.002



MIN AVG WALL: 0.030
MINIMUM WALL: 0.027

Stranding: 10/30 2% Nickel Plated Copper LHL

Style: UL: AWM 3172 CSA: SEWF-2

Insulation: Braided Silicone

Print Legend: 20 AWG (0.519mm²) E57498 (PLANT ID CODE) (AWM LOGO) AWM 3172 200C 600V -- 156205 CSA SEWF-2 200C 600V FT1

Voltage: 600V

Temperature: 200C

- Notes:**
1. Diameter shown is OD under braid.
 2. The OD over the braid is approximately 0.108".

This product complies with European Directive 2015/863 -- RoHS 3.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

Customer Approval:

Customer Part Nbr(s): _____

Approved By: _____ **Date:** _____

Title: _____ **Company Name:** _____



Southwire
Copperfield[®]
 1115 W. North Street
 Bremen, IN 46506
 Phone: 1-574-546-5115