PRODUCT SPECIFICATION

DATEREVECNDESCRIPTION6/6/2016BCorrected description.


Parent Number: F20137-

Description: 20 10/30 2% Nickel Plated AWM 3135 AWM I

A Braidless Silicone

DIAMETER: 0.103

TOLERANCE ± : 0.003



MIN AVG WALL: <u>0.030</u>

MINIMUM WALL: 0.027

Stranding: 10/30 2% Nickel Plated LHL

Style: UL: AWM 3135 CSA: AWM I A

Insulation: Silicone Rubber

Print Legend: 20 AWG (0.519mm2) E57498 (PLANT ID CODE) (AWM LOGO) AWM 3135 200C 600V --- 156205 CSA AWM I A 200C 600V FT2

Voltage: 600V

Temperature: 200C

Notes:

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

Customer Approval:		
Customer Part Nbr(s):		
Approved By:	Date:	
Title:	Company Name:	

Southwire*

Copperfield

1115 W. North Street Bremen, IN 46506 Phone: 1-574-546-5115