



MERCURY WIRE PRODUCTS, INC.
SPENCER, MASSACHUSETTS
Manufacturers of Wire & Cable

CABLE SPECIFICATION

MW#: 22302
 ENGINEERED BY: MA
 DATE: 6/5/2007
 SHEET 1 OF 1
 REVISION: 01

20/C #16 AWG RIBBON CABLE

Conductors: #16 AWG 19/29 tinned copper

Insulation: nominal .015" thickness, -27 to 105°C PVC


Color Code:	1.	Black
	2.	Brown
	3.	Red
	4.	Orange
	5.	Yellow
	6.	Green
	7.	Blue
	8.	Violet
	9.	Gray
	10.	White
	11.	White/Black
	12.	White/Brown
	13.	White/Red
	14.	White/Orange
	15.	White/Yellow
	16.	White/Green
	17.	White/Blue
	18.	White/Violet
	19.	White/Gray
	20.	White/Black/Brown

Cable Construction: (20) #16 AWG conductors are bonded together, parallel

Approximate Dimensions: .086" Minor x 1.72" Major

This product is compliant with Directive 2002/95/EU (RoHS) based on information provided to Mercury Wire Products, Inc. by our raw material vendors.

Cross Section



PACKAGING: BULK PUT-UPS, LONGEST LENGTHS POSSIBLE, 3 LENGTHS PER REEL MAXIMUM UNLESS OTHERWISE SPECIFIED ON PURCHASE ORDER. DIFFERENT PACKAGING MAY INCUR ADDITIONAL COSTS.

THE PHYSICAL AND ELECTRICAL CHARACTERISTICS CONTAINED IN THIS CABLE SPECIFICATION ARE BELIEVED TO BE RELIABLE AND ARE DERIVED FROM VENDOR SUPPLIED DATA AND INDUSTRY STANDARDS. AS EACH APPLICATION IS UNIQUE, MERCURY WIRE CAN MAKE NO WARRANTIES AS TO THE SUITABILITY OF ANY PRODUCT FOR A PARTICULAR USE.

ACCEPTED: _____
 COMPANY NAME

 NAME (PRINTED)

 DATE

 NAME (SIGNATURE)