

HITACHI CABLE AMERICA

Customer Specification

HCM - 23224/6

RFQ #: 46266

ITEM DESCRIPTION: .100 WIDE PITCH RIBBON CABLE, CONSISTING OF 6 CONDUCTOR, 24 AWG, UNSHIELDED, UNJACKETED. (UL) 2651, CSA I A/B

FLAT PRIMARY:

CONDUCTOR: 24 AWG 7/32 TINNED COPPER
.0228" NOM OD

INSULATION: PVC LF
GRAY

THE #1 CONDUCTOR IS MARKED WITH A RED POLARITY STRIPE.

AGENCY APPROVALS: U.L. RECOGNIZED AWM STYLE 2651, 105C, 300V.
USE: FOR INTERNAL WIRING OF ELECTRONIC EQUIPMENT (SUCH AS COMPUTERS AND ELECTRIC BUSINESS MACHINES) VW-1.

ENVIRONMENTAL COMPLIANCE*
ROHS - EU DIRECTIVE 2002/95/EC
REACH - EU REGULATION 1907/2006
*ALLOWABLE LIMITS SUBJECT TO CHANGE - COMPLIANT ON DATE OF LATEST REVISION OF HCM SPECIFICATION

TYPICAL ELECTRICAL CHARACTERISTICS:


S.E. IMPEDANCE: 130 OHM (G-S-G @ 3.5 ns)
CAPACITANCE: 13.0 pF/FT (G-S-G @ 1 KHz)
TIME DELAY: 1.35 ns/FT NOM
COND. RESISTANCE: 25.7 OHM/M' NOM @ 20°C

HITACHI CABLE AMERICA 900 Holt Avenue-East Industrial Park Manchester, N.H. 03109 (603) 669-4347	Drawn By: KDA Date: 10/25/12 Checked By: JME Date: 10/25/12 Issued By: KDA Date: 10/25/12	REV#
	THIS PRODUCT MADE IN THE U.S.A.	
ITEM: 23224-0006-XXX-XXX-802-S-01000-4745-00	PAGE 1 of 2 Approved By: Date:	

HITACHI CABLE AMERICA


Customer Specification

HCM - 23224/6



MARKING:

THE CABLE IS IDENTIFIED WITH THE FOLLOWING PRINT LEGEND:

**HITACHI CABLE AMERICA - HCM 23224  AWM STYLE 2651
24 AWG 300V 105C VW-1 - LL50890 CSA AWM I A/B 300V
105C FT1 - RoHS - ZZ/DD/YY HR:MN (XXXX)**

**WHERE: ZZ = MONTH OF MFG.
DD = DATE OF MFG.
YY = YEAR OF MFG.
HR = HOUR (MILITARY)
MN = MINUTE
XXXX = JOB NUMBER**