
Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION



FF3U06SD Modular Connectors - FX ULTRA FRAME



For more Information please call

1-800-Belden1



General Description:

FX ULTRA FRAME, OM3, 06 PORTS, SC DUPLEX, AQUA ADAPTERS

Usage (Overall)

Suitable Applications: FiberExpress Ultra Solutions, Backbone, Telecommunications Room, Main Distribution Room, Data Centers

Related Parts: FiberExpress Ultra Patch panels, Pre-terminated MPO low loss cable assemblies

Physical Characteristics (Connectivity)

Dimensions

Dimensions:

Height (in.)	Width (in.)	Depth (in.)
1.500	4.460	2.200

Materials

Materials:

Description	Туре	Material	Color
Frame		Plastic - UL94V-0	Black
Front Connector Body	SC-Duplex	Plastic - UL94V-0	Aqua
Adapter Sleeve		Zirconia-Ceramic	

Included Parts

Included Parts: Dust caps

Packaging

Packaging: Individually packaged in a plastic shell, Shipped in cardboard box (60/box)

Mechanical Characteristics (Connectivity)

Footprint/Type: 1 inch Pullout

Termination Interface:

Termination	Connection	Durabilities	
Front	Mated Connection	500 cycles	
Rear	Mated Connection	500 cycles	

 Cable/Connector Retention:
 11.250 lbs.

 Connector/Hardware Retention:
 11.250 lbs.

 Storage Temperature Range:
 -40°C To +75°C

 Operating Temperature Range:
 -10°C To +60°C

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

EU Directive 2002/95/EC (RoHS):

Page 1 of 2 11-05-2015

Detailed Specifications & Technical Data





FF3U06SD Modular Connectors - FX ULTRA FRAME

	EU RoHS Compliance Date (mm/dd/yyyy):	07/01/2006
	MII Order #39 (China RoHS):	EUP 50
Sui	tability	
	Suitability - Indoor:	Yes

Transmission Characteristics (Connectivity)

Notes (Overall)

Product Family

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
FF3U06SD	1 EA	0.030 LB			FXU FRAME OM3 06P
FF3U06SD-NPI	1 EA	0.030 LB			FXU FRAME OM3 06P

Revision Number: 0 Revision Date: 08-26-2014

© 2015 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sales.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. product.

> Page 2 of 2 11-05-2015