
# **Detailed Specifications & Technical Data**



# METRIC MEASUREMENT VERSION

# FF3U06SD Modular Connectors - FX ULTRA FRAME



For more Information please call

1-800-Belden1



### **General Description:**

# FX ULTRA FRAME, OM3, 06 PORTS, SC DUPLEX, AQUA ADAPTERS

sage (Overall)								
Suitable Applications:				FiberExpress Ultra Solutions, Backbone, Telecommunications Room, Main Distribution Room, Data Centers				
Related Parts:				FiberExpress Ultra Patch panels, Pre-terminated MPO low loss cable assemblies				
hysical Characterist	tics (Con	nectivity)						
Dimensions Dimensions:								
Height (mm) Width (n	nm) Depth (	(mm)						
38.100 113.284 55.880								
Materials Materials:								
Description	Туре	Material	Color					
Frame		Plastic - UL94V-0	I I					
	SC-Duplex	Plastic - UL94V-0	Aqua					
Adapter Sleeve		Zirconia-Ceramic						
ncluded Parts								
Included Parts:				Dust caps				
Packaging								
Packaging:				Individually packaged in a plastic shell, Shipped in cardboard box (60/box)				
lechanical Characte	ristics (C	connectivity)						
Footprint/Type:				1 inch Pullout				
Fermination Interface:								
Termination Connection		abilities						
Front Mated Conr								
Rear Mated Connection 500 cycles								
Cable/Connector Retention:				50.042 N				
Connector/Hardware Retention:				50.042 N				
Storage Temperature Range:				-40°C To +75°C				
Storage Temperature	-							

#### Applicable Specifications and Agency Compliance (Overall) **Applicable Standards & Environmental Programs** Yes

EU Directive 2002/95/EC (RoHS):

# **Detailed Specifications & Technical Data**



### METRIC MEASUREMENT VERSION

# FF3U06SD Modular Connectors - FX ULTRA FRAME

EU RoHS Compliance Date (mm/dd/yyyy):	07/01/2006
MII Order #39 (China RoHS):	EUP 50
Suitability	
Suitability - Indoor:	Yes

### Transmission Characteristics (Connectivity)

Notes (Overall)

Product Family

### **Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
FF3U06SD	1 EA	0.030 LB			FXU FRAME OM3 06P
FF3U06SD-NPI	1 EA	0.030 LB			FXU FRAME OM3 06P

#### Revision Number: 0 Revision Date: 08-26-2014

© 2015 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product tiself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. product.