



**GMW15626**  
**Single-Core Stranded ISO Cable**  
**FLR2X-A\_/T125**

**Features**

Conductors available in bare copper  
 Insulation: -40 to 125C Crosslinked Polyethylene  
 RoHS and REACH Compliant

**Applications**

Cables used for road vehicle applications  
 Nominal system voltage is < 60 VDC or 25 VAC

**Product Design Options**

Various colors for base and stripe combinations  
 Packaging options: reels or drums

Size mm <sup>2</sup>	Number of Strands	Strand Diameter (max)	Conductor Diameter (max)	Outside Diameter (min and max)		Insulation thickness (min)	Conductor Resistance (max and min)	
		mm	mm	mm		mm	mOhm/m	
0.35	7	0.27	0.90	1.20	1.40	0.20	54.40	50.00
0.5	19	0.19	1.10	1.40	1.60	0.22	37.10	34.10
0.75	19	0.24	1.30	1.70	1.90	0.24	24.70	22.70
1	19	0.27	1.50	1.90	2.10	0.24	18.50	17.00
1.5	19	0.33	1.80	2.20	2.40	0.24	12.70	11.70
2	19	0.38	2.00	2.50	2.80	0.28	9.42	8.66
2.5	37	0.28	2.20	2.70	3.00	0.28	7.60	6.99
3	37	0.34	2.40	3.10	3.40	0.32	6.15	5.66
4	37	0.38	2.80	3.40	3.70	0.32	4.71	4.33
5	37	0.43	3.10	3.90	4.20	0.32	3.94	3.62
6	37	0.45	3.40	4.00	4.30	0.32	3.14	2.89
8	50	0.46	4.10	4.60	5.00	0.32	2.38	2.19
10	63	0.46	4.50	5.30	6.00	0.48	1.82	1.68

REV: - 0 - 2012-02-10

**Customer Service Group**

1 Prestolite Drive Paragould, Arkansas 72450

Phone: 800-952-3842 870-236-8141

Fax: 870-239-6139

Web: [www.prestolitewire.com](http://www.prestolitewire.com)