


DATE	REV	ECN	DESCRIPTION
7/14/2016	D		Updated OEM designations.

**PRODUCT SPECIFICATION**

**Parent Number:** FMC007-

**Description:** 0.35mm<sup>2</sup> 7/.25mm BC Thin Wall 2TAD ES-AU5T-1A348-AA Ford Global Spec FLYR-A Class 2

**DIAMETER:** 0.051  
**TOLERANCE ± :** 0.004



**NOM WALL:** 0.010  
**MINIMUM WALL:** 0.008

**Stranding:** 7/.25mm BC LHL

**Style:** Ford: ES-AU5T-1A348-AA 2TAD; GM: GMW15626 CU-R2PVC; Chrysler: MS.90034 5ABT; FLYR-A

**Insulation:** PVC

**Print Legend:** NO PRINT

**Voltage:** Nominal system voltage of 60 V rms or less in automotive electrical harnesses.

**Temperature:** -40C to +105C

**Notes:**

This product complies with European Directive 2015/863 -- RoHS 3.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.



**Copperfield<sup>®</sup>**

1115 W. North Street  
 Bremen, IN 46506  
 Phone: 1-574-546-5115

**Customer Approval:**  
**Customer Part Nbr(s):** \_\_\_\_\_  
**Approved By:** \_\_\_\_\_ **Date:** \_\_\_\_\_  
**Title:** \_\_\_\_\_ **Company Name:** \_\_\_\_\_

