


PRODUCT SPECIFICATION

DATE	REV	ECN	DESCRIPTION
10/13/2016	E		Updated style section.

Parent Number: **FMD032-**

Description: 0.5mm2 19/.18mm BC Thin Wall 2TAD ES-AU5T-1A348-AA Ford Global Spec FLYRY-A ISO 6722-1

DIAMETER: 0.061
TOLERANCE ±: 0.002



NOM WALL: 0.011
MINIMUM WALL: 0.009

Stranding: 19/.18mm BC LHL

Style: Ford: ES-AU5T-1A348-AA 2TAD; GM: GMW15626 CU-R2PVC; Chrysler: MS.90034 5CBT; ISO 6722-1; DIN 76722 FLYRY 0.5-A I105

Insulation: PVC

Print Legend: NO PRINT

Voltage: Nominal system voltage of 60 V rms or less in automotive electrical harnesses.

Temperature: -40C to +105C

Notes:

This product complies with European Directive 2011/65/EU (RoHS 2)

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

Customer Approval:

Customer Part Nbr(s): FLRYA-5-4

Approved By: *[Signature]* Date: 5-1-17

Title: Sourcing Specialist Company Name: IEWC



Copperfield

1115 W. North Street
Bremen, IN 46506
Phone: 1-574-546-5115