PRODUCT SPECIFICATION

DATE	REV	ECN	DESCRIPTION
12/3/2015	Е		Added Fiat Chrysler designation.

Parent Number: FMD026-


Description: 0.5mm2 16/.20mm BC TW 2TBD ES-AU5T-

1A348-AA Ford Global Spec FLRY-B per

GMW15626 5BBT per Chrysler MS.90034

DIAMETER: 0.061

TOLERANCE + : 0.002



NOM WALL: 0.011

MINIMUM WALL: 0.009

Stranding: 16/.20mm BC LHL

Style: Ford: ES-AU5T-1A348-AA 2TBD; GM: GMW15626 Flry-B; Fiat

Chrysler: MS.90034 5BBT; ISO 6722: Din 72551

Insulation: PVC

Print Legend: NO PRINT

Voltage: Nominal system voltage of 60 V rms or less in automotive electrical harnesses.

Temperature: -40C to +105C

Notes:

This product complies with European Directive 2011/65/EU (RoHS 2)

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

Customer Approval:

Customer Part Nbr(s):		
Approved By:	Date:	
Title:	Company Name:	



Copperfield[®]

1115 W. North Street Bremen, IN 46506 Phone: 1-574-546-5115