

THERM-O-LINK INC.

10513 Freedom Street
GARRETTSVILLE, OHIO 44231

(330) 527-2124
FAX: (330) 527-2123

Material Specification

Customer: IEWC

TOL Spec ID: 2/C- 1037

Description: (2) Conductor Round Cable with 2 / 0.75mm(18Ga)
FLY 105 DegC PVC Inners, PVC 85C Jacket

Inners: FLY-0.75mm-24-B (Blk) / FLY-0.75mm-24-B(Wht)
PVC 105 DegC Insulated.

Stranding: 24 x .0076" Bare Lay = 1.0"
Insulation OD = .088" (min) / .091" (nom)
Minimum Avg Wall = .019"

Jacket: PVC, 85 DegC Jacket
(Pressure Extruded)

Jacket OD = .233" (Minimum) / .241" (Maximum)
Jacket Wall = .020" (Minimum)
Jacket Color: Black
Cable Lay: 2.5"
Separator: Talc powder
Fillers : None

This Product is RoHS Compliant.

Specification Reference Data

SAE: N/A	Ford: N/A	Chrysler: N/A
UL : N/A	CSA: N/A	Packard: N/A
Other: ISO 6722-1 (Metric Spec)		

Therm-O-Link, Inc. certifies that the above specifications are met or exceeded in the production of this product.

Verified By: Mir Hussain (Corporate Quality Engineer)

Date: 1-14-2015