



FOSC450-D6-6-NT-0-DOV | A42788-000

**FOSC™450 D6 Fiber Optic Splice Closure, Gel Cable sealing, no pre-installed tray, 6 cable attachments, with test valve**

- Single-ended, O-ring sealed dome closure for splicing feeder and distribution cables
- Gel cable sealing technology allows easy adding or removing of a wide size range of cables
- Compatible with most common cable types: e.g. loose tube, central core, ribbon fiber
- FOSC splice trays hinged for access to any splice without disturbing other trays
- Closure can be used in aerial, pedestal and underground (up to 5 meters) environments
- Compatible with CommScope's CWDM modules and optical splitter trays

## Body Features

Cable Seal	Compressed Gel
Color	Black

## Configuration Features

Port Shape	Round (6)
Flash Test Valve	Yes
Number of Pre-installed Splice Trays	none
Number of Cable Attachments	6
Slack Basket	Yes

## Dimensions

Closure Diameter	292.000 mm   11.496 in
Length	753.00 mm   29.65 in

## Packaging Features

Minimum Order Quantity	1
Packaging Method	Box/Carton

## Product Availability

Region	Latin America   North America
--------	-------------------------------

## Product Type Features

System	FOSC 450
Product Type	Butt Feeder & Distribution Closure

## Regulatory Compliance/Certifications

<b>Agency</b> RoHS 2011/65/EU	<b>Classification</b> Compliant
----------------------------------	------------------------------------