


Lutze TOP-T Fittings Metric

Plastic Metric



Characteristics:

- Integrated strain relief
- Wide sealing and clamping range
- Easy to install
- Manufactured according to EN 50262 requirements
- Temperature range -30°C - +80°C / -22°F - +176°F
- Max temporary temperature up to +150°C/+300°F
- Protection class IP68

Fitting Specifications:

Connecting thread	Metric as per EN 60423
Material	Polyamide 6
Seal	Neoprene
Color	Black RAL 9005 Gray RAL 7001

Part No.	Thread	Clamping Range Ø inch	Clamping Range Ø mm	TL mm	D/SW mm	TD mm	H mm
BLACK							
FPM12B	M12x1.5	0.118-0.256	3-6.5	8	15	12	22
FPM16B	M16x1.5	0.197-0.394	5-10	10	22	16	28
FPM20B	M20x1.5	0.315-0.551	10-14	10	27	20	31
FPM25B	M25x1.5	0.512-0.709	13-18	10	33	25	35
FPM32B	M32x1.5	0.709-0.984	18-25	18	42	32	40
FPM40B	M40x1.5	0.866-1.260	22-32	18	53	40	49
FPM50B	M50x1.5	1.181-1.496	30-38	18	60	50	49
FPM63B	M63x1.5	1.339-1.732	34-44	18	65	63	49
GRAY							
FPM12G	M12x1.5	0.118-0.256	3-6.5	8	15	12	22
FPM16G	M16x1.5	0.197-0.394	5-10	10	22	16	28
FPM20G	M20x1.5	0.315-0.551	10-14	10	27	20	31
FPM25G	M25x1.5	0.512-0.709	13-18	10	33	25	35
FPM32G	M32x1.5	0.709-0.984	18-25	18	42	32	40
FPM40G	M40x1.5	0.866-1.260	22-32	18	53	40	49
FPM50G	M50x1.5	1.181-1.496	30-38	18	60	50	49
FPM63G	M63x1.5	1.339-1.732	34-44	18	65	63	49
REDUCED CLAMPING RANGE							
FPM12G-R	M12x1.5	0.079-0.197	2-5	8	15	12	22
FPM16G-R	M16x1.5	0.118-0.276	3-7	10	22	16	28
FPM20G-R	M20x1.5	0.276-0.472	7-12	10	27	20	31
FPM25G-R	M25x1.5	0.354-0.630	9-16	10	33	25	35
FPM32G-R	M32x1.5	0.472-0.787	12-20	18	42	32	40
FPM40G-R	M40x1.5	0.787-1.024	20-26	18	53	40	49
FPM50G-R	M50x1.5	0.984-1.220	25-31	18	60	50	49
FPM63G-R	M63x1.5	1.142-1.378	29-35	18	65	63	49