



Lutze TOP-T Fittings NPT •

791003

Plastic NPT



Part No.	Thread A	Clamping Range Ø C	L mm	SW1 mm	SW2 mm	H mm
FITTINGS GRAY						
FPNPT38G	NPT 3/8"	5-10	15.5	22	22	44.5
FPNPT12G	NPT 1/2"	10-14	15	27	27	47.5
FPNPT34G	NPT 3/4"	14-18	15	33	33	52
FPNPT10G	NPT 1"	19-25	18	42	42	60.5

FITTINGS BLACK						
FPNPT38B	NPT 3/8"	5-10	15.5	22	22	44.5
FPNPT12B	NPT 1/2"	10-14	15	27	27	47.5
FPNPT34B	NPT 3/4"	14-18	15	33	33	52
FPNPT10B	NPT 1"	19-25	18	42	42	60.5

REDUCED CLAMPING RANGE						
FPNPT38B-R	NPT 3/8"	3-7	15.5	22	22	44.5
FPNPT12B-R	NPT 1/2"	7-12	15	27	27	47.5
FPNPT34B-R	NPT 3/4"	9-16	15	33	33	52
FPNPT10B-R	NPT 1"	12-20	18	42	42	60.5

LOCKNUTS GRAY						
LPNPT38G	NPT 3/8"			22		5
LPNPT12G	NPT 1/2"			27		6
LPNPT34G	NPT 3/4"			36		7
LPNPT10G	NPT 1"			42		7

LOCKNUTS BLACK						
LPNPT38B	NPT 3/8"			22		5
LPNPT12B	NPT 1/2"			27		6
LPNPT34B	NPT 3/4"			36		7
LPNPT10B	NPT 1"			42		7

Characteristics:

- Integrated strain relief
- Wide sealing and clamping range
- Easy to install
- Temperature range -20°C - +100°C / +14 - +212 F
- Protection Grade IP68 - 5 bar

Fitting Specifications:

Dome nut	Polyamide PA6 V-2
Sealing Ring	Polychloroprene-Nitrile rubber CR/NBR
Gland body	Polyamide PA6 V-2
Connecting thread	NPT
Color	Black Gray RAL 7001

Locknut specifications:

- For secure tightening of cable glands and accessories
- Hexagonal locknut Polyamide PA6 GF30
- Internal thread NPT

1-800-447-2371 - www.lutze.com

